

**PART NUMBER: OUT-Q-CL-03**

## FIBER OPTIC SPLICE CLOSURE



This closure is a Fiber Infrastructure System Technology.

The generic closure is the environmentally sealed enclosure for the fiber management system that provides the functions of splice and passive component integration in the external network.



## FEATURES

- Single ended design
- Base and dome are sealed with a clamp and o-ring system
- 3 round entry/exit ports for drop cables and 1 oval port for looped cable
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- Uncut fibers can be stored as single circuits in trays and/or as cable elements in the storage space between the profiles.
- Storage baskets are available for mass storage of fibers of central core cable construction



## TECHNICAL SPECIFICATION

Number of oval port	1
Number of round ports	3
Max Fiber Capacity	Up to 48 F.O.
Closure Tray Capacity (Max)	4
Overall Closure Diameter (mm)	188
Overall Closure Height (mm)	300
Oval port max cable diameter (mm)	20
Round port max cable diameter (mm)	16

## CLOSURE KIT CONTENT

Closure (Base, Dome, Clamp)
Pre-mounted ground feed-through
Pre-mounted Pressure Testing Valve
Oval port sealing kit

## ACCESSORIES

Round port sealing kit
Oval port sealing kit
Wall/pole fixing bracket