

PART NUMBER: OUT-FOSM-740

740 FTTX FUSION SPLICER



STANDARD PACKAGE

- Main Body
- Spare Electrodes
- Fiber Cleaver
- Cooling Tray
- Drop Cable Stripper
- Manual Instruction
- Heater Device for Connector
- Carry Case
- Connector Holder
- Charger

PRODUCT FEATURES

- High definition LCD display
- Compact & Light weight
- PAS technology
- Core alignment
- Applied for Fibers, Cables and SOC (splice-on connector)
- Lithium battery
- Splicing method: auto, manual
- USB interface

TECHNICAL SPECIFICATION

Applicable fibers	SM, MM, NZ-DS(G655), EDF, G657 Low loss, Pigtail, Drop cable and connector.
Average splice loss	0.02dB(SM)、0.01dB(MM), 0.04dB(DS), 0.04dB(NZDS)
Return loss	≥60dB
Tension test	2.0N (200gf) (Standard)
Protection sleeve length	20mm, 40mm, 60mm and other series micro protection sleeves
Splicing program	80 groups
Language	English, Chinese, Russian, Spanish, Portuguese
Environment conditions:	-25~+50°C (operation temperature), 0~95%RH (humidity), 0~5000m (altitude)
Storage environment	-40~+80°C (temperature) , 0~95%RH (humidity)
Power supply	AC adaptor: 85~260V input voltage Internal battery: 12V,6Ah, up to 120 times of continuous splice and heat
Dimensions/Weight	142 (D) ×122 (W) ×138 (H) mm/1.95kg