



The 96-SPLICES, 8-round input + 1-oval input FOSC-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-B-8-TrayA-4 / FOSC type up to 96 splices with 8 circular input and 1 oval input

TECHNICAL FEATURES

OVAL INPUTS	1
ROUND INPUTS	8
OVERALL DIAMETER (INCLUDING CLAMP)	160 mm
OVERALL HEIGHT (INCLUDING BASE)	530 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE OVAL INPUT	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 8 PCS ROUND INPUT	7-10 mm
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to 96 F.O.

