

The 128 FO CRO has been developed for the outdoor infrastructure and it is configured for the termination of primary and secondary network cables. Even if the dimension of this cabinet is very small and compact, it still can host up to 128 HH (secondary network). It can host 1x2, 1x4 and 1x16 HGLX splitters.

It's external case, including door and roof, can be dismantled in case of damage without interrupting the connections inside.



PRODUCT CODE

MINICRO-FC-2020-V1

TECHNICAL FEATURES

MATERIAL	EXTERNAL PARTS: SUS 304 sp 1,5 mm DOOR: SUS 304 sp 1,2 mm INTERNAL PARTS: SUS 430 sp 1,2 mm
EXTERNAL DIMENSIONS	1220x335x300mm (AxLxP)
COLOR	Cabinet: RAL7037 Dusty Grey Roof: RAL 3020 Traffic Red
ADAPTERS QTY	128 + 48 SC/APC (secondary network + primary network)
SPLICE TRAYS QTY	16 + 6 grey color (splicing + secondary network parking) 6 + 4 red color (splicing + primary network parking)
SPLITTER QTY	up to 8 secondary splitters 1:16 up to 8 primary splitters 1:2 or 1:4
LOCK TYPE	Handle with three-point locking system Lock with Sicurvite profile