



Product **Catalog**



Catalogo Out Line

Versione Documento 3.0

Tel. +39 0690405273

info@outline.company - www.outline.company

Via degli Olmetti, 39D - 00060 Formello (RM)

INDICE **PRODOTTI**



1 Fiber Componets

ADAPTER SC SIMPLEX	.10
ADAPTER SC DUPLEX	.11
ADAPTER DUPLEX	. 12
ADAPTER QUAD	. 13
PATCHCORD SC/APC	14
PATCHCORD SC/APC 2MM	. 15
PATCHCORD SC/APC 3MM	. 16
PIGTAIL SC	. 17
PIGTAIL LC	18
KIT PIGTAIL SC/APC	19
MTP/MPO TRUNK CABLE	. 20
MTP/MPO FANOUT CABLE	
OPTICAL FBG REFLECTOR MONODIRECTIONAL TIM	
OPTICAL FBG REFLECTOR MONODIRECTIONAL/BIDIRECTIONAL OF	
CONNECTORS FAST MECHANICAL CONNECTOR SC/APC	
CONNECTORS SPLICE-ON CONNECTORS (SOC) SC/APC	. 25
CONNECTORS MECHANICAL JOINT	
CONNECTORS HEAT-SHRINKABLE TUBE	27
PLC SPLITTER PLANAR LIGHTWAVE CIRCUIT	28
PLC SPLITTER PLC SECONDARY SPLITTER FOR ROE UNIFIED TIM	
PLC SPLITTER SECONDARY SPLITTER	30
PLC SPLITTER SECONDARY HGLX SPLITTER	31
PLC SPLITTER SECONDARY SPLITTER	32
CWDM SECONDARY SPLITTER FOR UNIFIED ROE	
CWDM CEX FILTER MODULE FOR FTTH	.34
CENTERED CONTROL OF THE CONTROL OF T	\cup

\ensuremath{CWDM} wdm module pre-installed in fist type tray	35
RFID TAGS RFID.	36
SPLICE TRAYS KIT 4 SLE FIST TYPE	37
SPLICE TRAYS KIT 4 SC FIST TYPE	38
SPLICE TRAYS KIT 8 SC FIST TYPE	39
SPLICE TRAYS KIT 4 SE FIST TYPE	40
SPLICE TRAYS KIT 2 COMPACT SE SPLITTER TRAYS	41
SPLICE TRAYS KIT 2 COMPACT SE FOR 12 MICRO-SMOUV	42
SPLICE TRAYS KIT 2 COMPACT SE TRAYS FOR 24 MICRO-SMOUV	43
SPLICE TRAYS KIT 4 COMPACT SC TRAYS FOR 6 MICRO-SMOUV	44
SPLICE TRAYS KIT 4 COMPACT SC TRAYS FOR 12 MICRO-SMOUV	45

2 FTTH - FTTR

FTTH FIBER TO THE HOME	8
PRIMARY FLOOR DIVIDER	0
FTTH IN-BUILDING PRODUCTS SECONDARY FLOOR DIVIDER	1
FTTH IN-BUILDING PRODUCTS MINI FLOOR-BOX	2
FTTH IN-BUILDING PRODUCTS PROTECTIVE TUBE	3
FTTH IN-BUILDING PRODUCTS SPLICE PROTECTION SYSTEM	4
USER OPTICAL SOCKET (OTO) OPEN FIBER OTO	5
USER OPTICAL SOCKET (OTO) HYBRID (COPPER / FIBER) OTO	6
USER OPTICAL SOCKET (OTO) VDSL2 (CBS) SOCKET	7
USER OPTICAL SOCKET (OTO) OPTILINK - REEL WALL OUTLET	8
USER OPTICAL SOCKET (OTO) REEL WALL OUTLET	9
USER OPTICAL SOCKET (OTO) PLESIO - DIN	0
USER OPTICAL SOCKET (OTO) 4 FO OTO	1
FTTH SILWAY	

3 Optical Distribution box

ROE - 8 U.I. PER MURO/PALO
OPTICAL DISTRIBUTION BOX ROE 16 HH
OPTICAL DISTRIBUTION BOX ROE 16 HH - INTERNAL FRUIT
OPTICAL DISTRIBUTION BOX ROE 32 HH
OPTICAL DISTRIBUTION BOX ROE 32 HH - INTERNAL FRUIT
OPTICAL DISTRIBUTION BOX ROE 48 HH
OPTICAL DISTRIBUTION BOX ROE UNI 16 HH
OPTICAL DISTRIBUTION BOX ROE UNI 16 HH - INTERNAL FRUIT
OPTICAL DISTRIBUTION BOX PTE UNI 24 HH
OPTICAL DISTRIBUTION BOX PTE UNI 24 HH - INTERNAL FRUIT
PUNTO DI TERMINAZIONE DI EDIFICIO ROE UNI 32 HH
PUNTO DI TERMINAZIONE DI EDIFICIO ROE UNI 32 HH - INTERNAL FRUIT
PUNTO DI TERMINAZIONE DI EDIFICIO PTE UNI 48 HH
PUNTO DI TERMINAZIONE DI EDIFICIO PTE UNI 48 HH – INTERNAL FRUIT
OPTICAL DISTRIBUTION BOX PTE 8/16/24 HH
FO BOX 12 USERS
FO BOX ODB 24 HH
FO BOX ODB 48 HH
DIN FO BOX OPTICAL BOX DIN FIXING
DIN FO BOX OPTICAL BOX DIN FIXING 87
DIN FO BOX OPTICAL BOX DIN FIXING88

4 Fiber Optic Closures

SPLICES / 3+1 INPUT	92
OPTICAL CLOSURE 288-SPLICES / 6+1 INPUTS	93
OPTICAL CLOSURE 288-SPLICES / 16+1 INPUTS	94
OPTICAL CLOSURE 96-SPLICES / 8+1 INPUTS	95
OPTICAL CLOSURE 96-SPLICES / 4+1 INPUTS	96
OPTICAL CLOSURE COMPATTA COMPACT 96-SPLICES / 4+1 INPUTS	97
OPTICAL CLOSURE COMPATTA 96-SPLICES / 8+1 INPUTS	98

5 Fiber Optic Outdoor cabinet

F.O. OUTDOOR CABINET CRO 128 FO	102
F.O. OUTDOOR CABINET CRO 384 FO	103
F.O. OUTDOOR CABINET CRO 576 FO	104
F.O. OUTDOOR CABINET	
F.O. OUTDOOR CABINET PFS 3	
F.O. OUTDOOR CABINET PFS 4	
F.O. OUTDOOR CABINET PFS 144	
F.O. OUTDOOR CABINET SCP	
F.O. OUTDOOR CABINET NEW SCP - POLE MOUNTING	
F.O. OUTDOOR CABINET SCP-DG CABINET	
F.O. OUTDOOR CABINET PASSIVE ACCESS NODE (PAN)	
F.O. OUTDOOR CABINET FWA	
F.O. OUTDOOR CABINET CABINET IP 65 - 30RU	
F.O. OUTDOOR CABINET CABINET IP 55 - 34RU	
F.O. OUTDOOR CABINET CABINET IP 55 STANDARD	

6 Data Center and Data Rooms

6.1 Rack/ODF	
Rack/ODF	
NETWORKING RACKS	122
Rack/ODF DATA CENTER AND SERVER RACKS	124
Rack/ODF WMA (WALL MOUNTING ASSEMBLED) RACKS	126
RACK/ODF WMD (WALL MOUNTING DISASSEMBLED) RACKS	127
DATA ROOMS AND DATA CENTERS ODF DISTRIBUTION FRAME	128
6.2 IN-ROW STRUCTURES	
DATA ROOMS AND DATA CENTERS MODULAR IN-ROW MULTI-LAYER STRUCTURE FOR DATA ROOMS	132
6.3 CABLE DUCTS	
FIBER MANAGEMENT YELLOW FIBER DUCTS	136
6.4 ENERGY MANAGEMENT 6.4.1 - PDU 48VCC	•
PDU - 48VCC 8+8 MULTI-USER 48VDC SMART PDU - 3RU	138
PDU - 48VCC 4+4 MULTI-USER 48VCC SMART PDU - 4RU	139
PDU - 48VCC 2+2 MULTI-USER 48VDC PDU - 3RU	140
PDU - 48VCC 5+5 MULTI-USER 48VDC PDU - 3RU	141
6.4.2 - 230 Vac	
PDU - 230 VAC PDU 230VAC 10 LINEE	142
PDU - 230 VAC HEAD-ROW ELECTRIC PANEL QCC 630A	143
PDU - 230 VAC AUTOMATIC TRANSFER SWITCH (ATS)	144
PDU - 230 VAC DATA CENTER POWER DISTRIBUTION UNITS	145

6.5 FIBER OPTIC MANAGEMENT

FO CABLE MANAGEMENT U-SHAPE	148
MOC 24 24SC PIVOT SUBRACK	149
MOC 48 48SC PIVOT SUBRACK	150
SUBRACK TERMINATION/PATCHING OPEN FIBER	151
SUBRACK JUNCTION/TERMINATION OPEN FIBER/INFRANEL	152
SUBRACK 24 ADAPTER SC SIMPLEX	153
SUBRACK PIVOT 144 ADAPTERS SC SIMPLEX	
MOC 12 12SC PIVOT SUBRACK	155
SPLICE TRAY 12 FO WHITE	156
SPLICE TRAY 24 FO BLACK	157
MPO 4 MODULES SUBRACK	158
MPO MPO/LC MODULE	159
MPO SUBRACK 144 FO MPO	160
MPO 10 FRONT PANEL FOR 4 MPO/LC MODULES	161
MPO BLANK PANEL FOR MODULES	162
MPO PANEL FOR 4 MPO ADAPTER	163
PATCH PANEL RJ45 PATCH PANEL - 24 FTP PORTS	164
PATCH PANEL RJ45 PATCH PANEL - 24 UTP PORTS	165
PATCH PANEL RJ45 KEYSTONE JACK RJ45 UTP	166
RACK ACCESSORIES CABLE MANAGEMENT PANEL 1U	167
RACK ACCESSORIES FLEXIBLANK - 4U FLEXIBLE BLANK PANEL	168

7 Fiber Optic Cables

MICRODUCTS AND ACCESSORIES SINGLE MICRODUCTS	72
MICRODUCTS AND ACCESSORIES FENDER MULTI-DUCTS	73
MICRODUCTS AND ACCESSORIES FENDER MULTI-DUCTS	74
MICRODUCTS AND ACCESSORIES MICRODUCTS CUTTER	75
MICRODUCTS AND ACCESSORIES MICRODUCTS CONNECTORS	76
MICRODUCTS AND ACCESSORIES MICRODUCTS END CAPS	77
MICRODUCTS AND ACCESSORIES MICRODUTS REDUCER	78
MICRODUCTS AND ACCESSORIES MICRODUTS SEALING FOR MICROCABLES	79
SINGLE CABE OUTDOOR APPLICATION18	80
SINGLE CABE INDOOR APPLICATION18	81
RISER CABLE OUTDOOR APPLICATION	82
RISER CABLE INDOOR APPLICATION	83
AERIAL CABLES ADSS	84
AERIAL CABLES ADSS	
AERIAL CABLES ADSS DROP CABLE 24-48	86

8 Fiber Optic Instruments

SPLICING MACHINES CLADDING ALIGNMENT - FTTH	190
SPLICING MACHINES CORE ALIGNMENT - FTTH	191
MICRODUCTS AND ACCESSORIES FIBER CLEAVER FOR FMC	192
INSTRUMENTS FIELD OPTICAL SOURCE	193
INSTRUMENTS FIELD POWER METER	194
INSTRUMENTS VISUAL FAULT LOCATOR	195
ISTRUMENTS AND TOOLS FIBER OPTIC STRIPPER	196
ISTRUMENTS AND TOOLS MILLER KLEVAR CUTTER	196
ISTRUMENTS AND TOOLS LC CONNECTOR CLEANING PEN 1-CLICK	196

CONNECTOR CLEANING PEN 1-CLICK
RUMENTS AND TOOLS SER OPTIC CABLE STRIPPER
RUMENTS AND TOOLS AX AND COPPER CABLE STRIPPER196
RUMENTS AND TOOLS PROPYL ALCOHOL CLEANING WIPES -KIMTECH
RUMENTS AND TOOLS TOMATIC ALCOHOL DISPENSING BOTTLE197
RUMENTS AND TOOLS VLAR CUTTER
RUMENTS AND TOOLS NIBREAKOUT CABLE STRIPPER LONGITUDINAL
RUMENTS AND TOOLS CROSCOPE 400X W/2.2197



FIBER COMPONENTS



SC SIMPLEX



The SC Simplex Adapter for optical fiber allows a simple and fast connection between two connectors, it is designed to ensure the alignment between the fibers which maximizes the passage of light inside.









PRODUCT CODE			
AD-1-SCP-SCP-S-F	AD-1-SCA-SCA-S-F	AD-1-SCP-SCP-S-N	AD-1-SCA-SCA-S-N
WITH F	LANGES	FLAN	GELESS

TECHNICAL FEATURES	
DURATION (INSERTION CYCLES)	1000
WORKING TEMPERATURES	da -40C° a +85C°
MATERIALS	UL94-V0
ADAPTER COLOR	
SM PC	Blue
SM APC	Green
CARATTERISTICHE	
SLEEVE MATERIALS	Zirconia (SM)
TYPICAL INSERTION LOSS (dB)	-
SM PC (@1310 - 1550nm)	0,10
SM APC (@1310 - 1550nm)	0,10







ADAPTER


SC DUPLEX



The SC Duplex Adapter for optical fiber allows a simple and fast connection between couples of connectors, it is designed to ensure the alignment between the fibers which maximizes the passage of light inside.









PRODUCT CODE			
AD-2-SCP-SCP-S-F	AD-2-SCA-SCA-S-F	AD-2-SCP-SCP-S-N	AD-2-SCA-SCA-S-N
WITH FL	ANGES	FLAN	GELESS

TECHNICAL FEATURES	
DURATION (INSERTION CYCLES)	1000
WORKING TEMPERATURES	da -40C° a +85C°
MATERIALS	UL94-V0
ADAPTER COLOR	
SM PC	Blu
SM APC	Verde
CARATTERISTICHE	
SLEEVE MATERIALS	Zirconia (SM)
TYPICAL INSERTION LOSS (dB)	-
SM PC (@1310 - 1550nm)	0,10
SM APC (@1310 - 1550nm)	0,10







LC DUPLEX



The LC Duplex Adapter for optical fiber allows a simple and fast connection between 4 LC connectors, it is designed to ensure the alignment between the fibers which maximizes the passage of light inside.









PRODUCT CODE			
AD-2-LCP-LCP-S-F	AD-2-LCA-LCA-S-F	AD-2-LCP-LCP-S-N	AD-2-LCA-LCA-S-N
WITH F	LANGES	FLAN	GELESS

TECHNICAL FEATURES	
DURATION (INSERTION CYCLES)	1000
WORKING TEMPERATURES	da -40C° a +85C°
MATERIALS	UL94-V0
ADAPTER COLOR	
SM PC	Blu
SM APC	Verde
CHARACTERISTICS	
SLEEVE MATERIALS	Zirconia (SM)
TYPICAL INSERTION LOSS (dB)	
SM PC (@1310 - 1550nm)	0,10
SM APC (@1310 - 1550nm)	0,10







LC QUAD



The LC Quad Adapter for optical fiber allows a simple and fast connection between 8 LC connectors, it is designed to ensure the alignment between the fibers which maximizes the passage of light inside.









PRODUCT CODE			
AD-4-LCP-LCP-S-F	AD-4-LCA-LCA-S-F	AD-4-LCP-LCP-S-N	AD-4-LCA-LCA-S-N
WITH FLANGES		FLAN	GELESS

TECHNICAL FEATURES	
DURATION (INSERTION CYCLES)	1000
WORKING TEMPERATURES	da -40C° a +85C°
MATERIALS	UL94-V0
ADAPTER COLOR	
SM PC	Blu
SM APC	Verde
CHARACTERISTICS	
SLEEVE MATERIALS	Zirconia (SM)
TYPICAL INSERTION LOSS (dB)	-
SM PC (@1310 - 1550nm)	0,10
SM APC (@1310 - 1550nm)	0,10








SC/APC 2MM



The 2,00 mm Optical Patchcord is a connectorized fiber optic cable that allows the connection between two points of a fiber optic network. Based upon customer request or technical specifications, it can be provided in different colors, different cable lengths and different types of connectors.



PRODUCT CODE

 $\begin{tabular}{ll} PC-1-SCA-SCA-SM-C-20-L-YE-0600 / 2MM Simplex 6 MT LSZH Gialla \\ PC-1-SCA-SCA-SM-C-20-L-YE-0300 / 2MM Simplex 3 MT LSZH Gialla \\ \end{tabular}$

QUA CAMBIEREI E METTEREI UNA COSTRUZIONE CODICE

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	Ø 2,0 mm
EXTERNAL JACKET	LSZH
REINFORCEMENT	ARAMIDIC YARNS
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	200N
CRUSHING RESISTANCE	150 N/100 mm
WORKING TEMPERATURE	-25°C/+70°C







SC/APC 3MM



The 3,00 mm Optical Patchcord is a connectorized fiber optic cable that allows the connection between two points of a fiber optic network. Based upon customer request or technical specifications, it can be provided in different colors, different cable lengths and different types of connectors.



PRODUCT CODE

PC-1-SCA-SCA-SM-C-30-L-WH-0150 / 3MM Simplex 1,5 MT LSZH White PC-1-SCA-SCA-SM-C-30-L-WH-6000 / 3MM Simplex 60 MT LSZH White PC-1-SCA-SCA-SM-C-30-L-YE-0053 / 3MM Simplex 0,53 MT LSZH Yellow

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	Ø 3,0 mm
EXTERNAL JACKET	LSZH
REINFORCEMENT	Aramidic Yarns
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	200N
CRUSHING RESISTANCE	150 N/100 mm
WORKING TEMPERATURE	-25°C/+70°C







SC/APC METALLIC REINFORCED



The Optical Patchcord with metal reinforcement is a connectorized fiber optic cable that allows the connection between two points of a fiber optic network. Based upon customer request or technical specifications, it can be provided in different colors, different cable lengths and different types of connectors.



PRODUCT CODE

PC-1-SCA-SCA-SM-C-30-LA-WH-0150 / 3MM Simplex 1,5 MT LSZH Metallic reinforced White

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	Ø 3,0 mm
EXTERNAL JACKET	LSZH
REINFORCEMENT	Aramidic Yarns + Metallic Reinforcement
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	250 N
CRUSHING RESISTANCE	3000 N/100mm
WORKING TEMPERATURE	-25°C/+70°C







SC



The Pigtail is a 900 μ m diameter fiber optic cable, connectorized on only one of the two ends. Depending on the needs, the Pigtail can be provided in different colors, different cable lengths and different types of connectors.





PRODUCT CODE

PT-1-SCP-SM-C-09-L-WH-200 / Pigtail SC/PC G657-A1, guaina 900um - White 2 MT LSZH easystrip **PT-1-SCA-SM-C-09-L-WH-200 /** Pigtail SC/APC G657-A1, guaina 900um - White 2 MT LSZH easystrip

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	900µm
EXTERNAL JACKET	LSZH
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	PC: >50dB - APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	5 N att. ≤0,01db/km
WORKING TEMPERATURE	-25°C/+70°C







LC



The Pigtail is a 900 μ m diameter fiber optic cable, connectorized on only one of the two ends. Depending on the needs, the Pigtail can be provided in different colors, different cable lengths and different types of connectors.





PRODUCT CODE

PT-1-LCA-SM-C-09-L-WH-200 / Pigtail LC/APC G657-A1, guaina 900um - Bianca 2 MT LSZH easystrip **PT-1-LCP-SM-C-09-L-WH-200** / Pigtail LC/PC G657-A1, guaina 900um - Bianca 2 MT LSZH easystrip

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	900μm
EXTERNAL JACKET	LSZH
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	PC: >50dB - APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	5 N att. ≤0,01db/km
WORKING TEMPERATURE	-25°C/+70°C








SC/APC



The Pigtail is a 900 μ m diameter fiber optic cable, connectorized on only one of the two ends. The Pigtail kit includes a set of colored fiber optic cables following a predetermined 'color code' configuration. This way it is easier to identify the individual fibers during installation, for example in an optical junction and/or termination subrack or box or closure.



PRODUCT CODE

PT-1-SCA-SM-C-09-L-MC-200-KIT / Guaina 900um 12 pcs colored + 12 pcs colored pins 2 MT LSZH tight

TECHNICAL FEATURES	
FIBER TYPE	SM-9/125 ITU-T G657 A
CABLE DIAMETER	900µm
EXTERNAL JACKET	LSZH
TYPICAL INSERTION LOSS	0,15 dB
TYPICAL RETURN LOSS	PC: >50dB - APC: >65dB
MINIMUM BENDING RADIUS	15 mm x Ø att. ≤0,03 dB
TRACTION RESISTANCE	5 N att. ≤0,01db/km
WORKING TEMPERATURE	-25 °C / +70 °C







TRUNK CABLE



The MTP/MPO Trunk cable is a fiber optical cable connectorized on both sides, it is designed to be used for specific applications in high-density environments, such as data centers.



PRODUCT CODE

SUPPLIED UPON CUSTOMER REQUEST AND SPECIFICATION.

TECHNICAL FEATURES	
FIBER TYPE	OS2 - OM3 - OM4
CABLE DIAMETER	3 mm
EXTERNAL JACKET	LSZH
FIBERS QTY	12 / 24
DYNAMIC BENDING RADIUS	20 x cable Ø
WORKING TEMPERATURE	25 °C / +70 °C
REINFORCEMENT	Aramidic Yarns








FANOUT CABLE



The Fanout cable is terminated on one side with an MTP/MPO connector, and on the other side, using an extremely small cable divider, it is terminated with SC or LC connectors.



PRODUCT CODE

SUPPLIED UPON CUSTOMER REQUEST AND SPECIFICATION.

TECHNICAL FEATURES	
FIBER TYPE	OS2 - OM3 - OM4
MICROCABLE EXTERNAL DIAMETER	3 mm
FANOUT EXTERNAL DIAMETER	2 mm
GUAINA	LSZH
EXTERNAL JACKET	12 24
FIBERS QTY	20 x cable Ø
REINFORCEMENT	Aramidic Yarns
WORKING TEMPERATURE	-25 °C / +70 °C
TEMPERATURA	-25°C/+70°C







OPTICAL FBG REFLECTOR

MONODIRECTIONAL TIM



Fiber Optical Reflectors with FBG Technology are used to check and verify any attenuation or inefficieny by creating reflectance at the end of a passive optical network (PON) without affecting data traffic at all.

The monodirectional model is used in the ODBs (like ROE or PTE or OTO) in order to verify the stability of the network till that point of the network, as much as close to the customer premises.

This product has been developed based on the TIM technical specification.



PRODUCT CODE

ORF-SC-FBG-S-PL / FBG-S Reflector (monodirectional with green plastic case) - NMU 773292

TECHNICAL FEATURES	
PASSING BANDWIDTH	Тур. 1260-1625
U BANDWIDTH	Тур. 1644.5-1655.5
INSERTION LOSS PASSING BANDWIDTH	≤ 1.5 DB
INSERTION LOSS U BANDWIDTH	Min. 20 dB
RETURN LOSS PASSING BANDWIDTH	Min. 22 dB
RETURN LOSS U BANDWIDTH	≤ 1.5 DB
PDL	≤ 0.5 DB
TDL	≤ 0.3 DB
WORKING TEMPERATURES	-25 °C / +70 °C
STORAGE HUMIDITY	5 / 95 %RH
CONNECTOR	SC/APC Male & SC/APC Female







OPTICAL FBG RFFL FCTOR

MONODIRECTIONAL/BIDIRECTIONAL OF



Fiber Optical Reflectors with FBG Technology are used to check and verify any attenuation or inefficieny by creating reflectance at the end of a passive optical network (PON) without affecting data traffic at all.

The monodirectional model is used in the ODBs (like ROE or PTE or OTO) in order to verify the stability of the network till that point of the network, as much as close to the customer premises.

The bidirectional model is used in the street cabinets for cross-connections. This These products have been developed based on the OPEN FIBER technical specification.





PRODUCT CODE

ORF-SC-FBG-S-PL-OF / FBG-S Reflector (monodirectional with green plastic case) - Open Fiber ST1825 **ORF-SC-FBG-S-BI** / FBG-S Reflector (bidirectional with magenta plastic case) - Open Fiber ST1825

TECHNICAL FEATURES	
PASSING BANDWIDTH	Тур. 1260-1625
U BANDWIDTH	Тур. 1644.5-1655.5
INSERTION LOSS (@ 1260 NM - 1360 MN @ 1460 NM - 1610 MN / @ 1610 NM - 1625 MN)	TYP. 0.8 dB (70%) - Max 1.0 dB (100%)
INSERTION LOSS BANDA RIFLESSIONE	Min 25 dB (100%) - TYP. 29 dB (70%)
RETURN LOSS (@ 1260 NM - 1360 MN @ 1460 NM - 1610 MN)	Min. 32 dB
RETURN LOSS @ 1610 NM - 1625 MN)	Min. 25 dB
RETURN LOSS U BANDWIDTH	MIN 0 db - MAX 1 dB
RIPPLE	≤ 0.6 dB
PDL	≤ 0.4 db
TDL	≤ 0.5 db
WORKING TEMPERATURES	-25 °C + 70 °-25 / +70
STORAGE HUMIDITY	5 / 95 %RH
CONNECTOR	SC/APC Male & SC/APC Female







FAST MECHANICAL CONNECTOR SC/APC



The fast mechanical connector can be easily mounted directly on the field, because allows a fast and simple mechanical splicing. A pre-polished ferule is supplied from the factory with all the accessories to complete the installation of the connector on a 900 µm cable.

Our connectors come in KIT which can include the support for cutting the fiber (holder) and the fiber cleaver itself.



PRODUCT CODE

OUT-CONN-920H-SCA-KIT / KIT COMPOSITION: 60 pcs Mechanical Connectors SC/APC + 1 Pc Fiber Cleaver - NMU 776764

OUT-CONN-920H-SCA / KIT COMPOSITION: 60 pcs Mechanical Connectors SC/APC

TECHNICAL FEATURES	
FIBERS COMPATIBILITY	850 ~ 950 μm
INSERTION LOSS	(@1310-1550 NM) ≤ 0.6 dB
RETURN LOSS	(@1310-1550 NM) ≥ 50 dB
INSTALLATION TIME	≥ 30 sec
FERULE	Pre-polished SC/APC
FIBER COUPLING SYSTEM	V-Grove (gel ottico)








SPLICE-ON CONNECTORS (SOC) SC/APC



Splice-On connectors SC/APC are field-installable and represent an ideal solution for fast installations and in particularly difficult context. This type of connectors offer a fast execution time without the need for special crimping systems but rather using the splicer machine that is usually equipped with a plastic holder to allow the splice between the connector itself and the chosen 900um or 250um fiber cable.



PRODUCT CODE

KIT-CONN-SOC-SCA / Splice-on SC/APC Connector for 250/900um fibers

TECHNICAL FEATURES	
FIBERS COMPATIBILITY	250/900 UM
INSERTION LOSS	Typ. 0.15 dB - Max 0.30 dB
RETURN LOSS	Min. 60 dB
FERULE	Pre-polished SC/APC
WORKING TEMPERATURES	-25 / +70 °C
DURABILITY (INSERTION CYCLES)	500 Cycles







MECHANICAL JOINT



The mechanical joint can be mounted on the field, by means of mechanical splicing. This component allows the alignment and connection between 250 um fibers, between cables with external jacket of 900um and in combination between the two typologies.



PRODUCT CODE

OUT-925 / Mechanical joint for 250/900 μm fibers

TECHNICAL FEATURES	
FIBERS COMPATIBILITY	250 μm - 900 μm
INSERTION LOSS	(@1310-1550 NM) ≤ 0.15 dB
RETURN LOSS	(@1310-1550 NM) ≥ 50 dB
INSTALLATION TIME	≥ 10 sec
FIBER COUPLING SYSTEM	V-Grove (gel)
DIMENSION	45X4X4.7mm
KIT COMPOSITION	25 pcs mechanical joints + 1 pc Holder







HEAT-SHRINKABLE TUBE



The heat-shrinkable tube (or Smouv) is a necessary product in the case of fiber optical cable splice joints as it allows the right protection of the spliced point itself from any mechanical stress and/or torsion that it may be subjected to.





PRODUCT CODE

SMV-MIC-35-100/ Metallic pin diameter 1,5mm with lenght 35mm (pack of 100 pcs) **SMV-STD-45-100**/ Metallic pin diameter 2,6mm with lenght 45mm (pack of 100 pcs)

TECHNICAL FEATURES	
LENGHT	35 mm 45 mm
INTERNAL HOLE DIAMETER	0.5 mm 1.3 mm
DEPTH	0.5 mm 1.2 mm
METALLIC PIN LENGHT	30 mm 45 mm
AFTER SHIRINK DIAMETER	1.6 mm 2.5 mm







PLANAR LIGHTWAVE CIRCUIT



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied with a small metal case, 250um buffer not connectorized and generally used in ODBs or Closures in point-to-multipoint topologies (PON networks). These products have been developed upon TIM and Open Fiber technical specification.



PRODUCT CODE

28

PLC-1X4-A-B/200-N-B/200-N-2 (D)/ PLC splitter 1x4 Input 2m, output 2m with deribonized fibers, 250um, G.657 A1, fibre no connectors, stainless steel module 4X4X40mm - N.M.U. TIM 880261 - S.T. 1703 V.1 Open Fiber

PLC-1X8-A-B/200-N-B/200-N-2 (D)/ PLC splitter 1x8 Input 2m, output 2m with deribonized fibers, 250um, G.657 A1, fibre no connectors, stainless steel module - N.M.U. TIM 775641

PLC-2X4-A-B/200-N-B/200-N-2 (D) / PLC splitter 2x4 Input 2m, output 2m, with deribonized fibers, 250um, G.657 A1, fibre no connectors, stainless steel module 4X4X40mm - N.M.U. TIM 768467

PLC-2X8-A-B/200-N-B/200-N-2 (D) / / PLC splitter 2x8 Input 2m, output 2m, with deribonized fibers, 250um, G.657 A1, fibre no connectors, stainless steel module 4X4X40mm - N.M.U. TIM 768468

PLC-2X16-A-B/200-N-B/200-N-2 (D) / PLC splitter 2x16 Input 2m, output 2m, with deribonized fibers, 250um, G.657 A1, ffibre no connectors, stainless steel module 4X4X40mm - N.M.U. TIM 768487

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1x4 - 1X8 - 2X4 - 2X8 - 2X16
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	7,2 dB - 10,7 dB - 7,7 dB - 11,2 dB - 14,7 dB
ATTENUATION UNIFORMITY	1.3 dB
RETURN LOSS	55 dB
PDL	Max 0.3 dB
TEMEPERATURE STABILITY	Var max 0,5 dB @ - 20 / + 70 °C
WORKING TEMPERATURES	- 20 °C / + 70 °C
FIBER DIAMETER	250 μm
FIBER LENGHT	Ingresso/Uscita 200 cm
PACKAGE TYPE	Mini Module Packaging Metal Box
CASE SIZE	40x4x4 - 50x5x4 - 50x4x4 - 50x4x4 - 60x7x4 mm
PACKAGE SIZE	40x4x4 - 50x5x4 - 50x4x4 - 50x4x4 - 60x7x4 mm







PLC SECONDARY SPLITTER FOR ROE UNIFIED TIM



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied with a small metal case, 900um buffer not connectorized and generally used in ODBs or Closures in point-to-multipoint topologies (PON networks). These products have been developed upon TIM technical specification.



PRODUCT CODE

PLC-1X4-A-09/105-SCA-09/095-SCA-2 / PLC splitter 1x4 Input 105cm, output 95cm, 0.9mm jacket, SC/APC connectors, stainless steel module - N.M.U. TIM 768678

PLC-1X8-A-09/105-SCA-09/095-SCA-2 / PPLC splitter 1x8 Input 105cm, output 95cm, 0.9mm jacket, SC/APC connectors, stainless steel module - N.M.U. TIM

PLC-1X16-A-09/105-SCA-09/095-SCA-2/ PLC splitter 1x16 Input 105cm, output 95cm, 0.9mm jacket, SC/APC connetors, stainless steel module - N.M.U. TIM 768615

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1X4 - 1X8 - 1x16
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	7.3 dB - 10.7 dB - 14.1 dB
RETURN LOSS	55 dB
PDL (DB)	± 0.2 dB - ± 0.3 dB - ± 0.3 dB
FIBER DIAMETER	900 μm
FIBER LENGHT	input 105 cm / output 95 cm
CASE TYPE	Mini Module Stainless steel
CASE SIZES	60x7x4 mm - 60x7x4 mm - 60x12x4 mm
CONNECTORS	SC/APC







SECONDARY SPLITTER



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied with a plastic black case, 1,6mm jacket, SC/APC pre-connectorized. Usually used in street cabinets like CNO or PFS3 in point-to-multipoint topologies (PON networks). These products have been developed upon OPEN FIBER technical specification.



PRODUCT CODE

PLC-1x16-A-16/150-SCA-16/150-SCA-3 / PLC splitter 1x16 BUTT type - in plastic box 100 x 80 x 10mm (L x H xP), G657A1, input 1.6mm no connector, output 1,6mm with connectors SC/APC - for CNO - ST INF-ING-ST-006-19 INFRATEL

PLC-1x16-A-16/150-N-16/150-SCA-3 / PLC splitter 1x16 BUTT type - in plastic box 100 x 80 x 10mm (L x H x P) , G657A1, input 1.6mm with connector SC/APC, output 1,6mm with connectors SC/APC - for PFS3 - ST 1716 Rev. V2.0 Open Fiber

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1x16
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	13.3 dB
RETURN LOSS	55 dB
PDL (DB)	± 0.5 dB
FIBER DIAMETER	1.6 mm
LENGHT	input 150 cm / output 150 cm
CASE TYPE	Plastic case
CASE SIZE	100x80x10 mm
CONNECTORS	SC/APC







SECONDARY HGLX SPLITTER



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied with HLGX metallic case which includes pre-installed adapters, input with 1,6mm jacket (connectorized or not), pre-cabled and connectorized SC/APC outputs. Usually used in street cabinets like PFS4, SCP in point-to-multipoint topologies (PON networks). These products have been developed upon TIM or OPEN FIBER technical specification.



PRODUCT CODE

HGLX splitter 1x16 - Metal/Plastic case 144 x 40 x 90mm (L x H x P), G657.A1, not-connectorized input 1.6mm with red color jacket, connectorized output SC/APC pre-installed on 16 SC/APC adapters. Compatible with PFS 4 / CRO series / PFS 144 / SCP (1st version)

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1x16
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	13.3 dB
RETURN LOSS	55 dB
PDL (DB)	± 0.5 dB
FIBER DIAMETER	1.6 mm
LENGHT	280 cm
CASE TYPE	Plastic or Metallic case
CASE SIZE	144x40x90 mm
CONNECTORS	Output SC/APC - Input SC/APC or Non connectorized








SECONDARY SPLITTER



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied in plastic case with SC/APC connectorized input with 900 μ m jacket, pre-cabled and connectorized SC/APC outputs with 900 μ m jacket. Usually used in ODBs in point-to-multipoint topologies (PON networks).



PRODUCT CODE

PLC-1X4-A-09/060-SCA-09/050-SCA-3-C04 / PLC splitter 1x4 tipo BUTT - in scatola plastica $100 \times 45 \times 10$ mm (L x H x P) , G657A1, input 0,9mm con connettore SC/APC, output 0,9mm con connettori SC/APC - per ROE Metroweb - V.S. 005_ Issue2 M.W.

PLC-1X8-A-09/060-SCA-09/050-SCA-3-C04 / PLC splitter 1x8 tipo BUTT - in scatola plastica 100 x 45 x 10mm (L x H x P) , G657A1, input 0,9mm con connettore SC/APC, output 0,9mm con connettori SC/APC - per ROE Metroweb - V.S. 005_Issue2 M.W.

PLC-1X16-A-09/060-SCA-09/050-SCA-3-C04 / / PLC splitter 1x16 tipo BUTT - in scatola plastica $100 \times 45 \times 10$ mm (L x H x P) , G657A1, input 0,9mm con connettore SC/APC, output 0,9mm con connettori SC/APC - per ROE Metroweb - V.S. 005 Issue2 M.W.

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1X4 - 1X8 - 1x16
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	7.3 dB - 10.7 dB - 14.1 dB
RETURN LOSS	55 dB
PDL (DB)	± 0.2 dB - ± 0.5 dB - ± 0.5 dB
FIBER DIAMETER	900 μm
LENGHT	Input 60 cm / Output 50 cm
CASE TYPE	Plastic box
CASE SIZE	100x45x10 mm
CONNECTORS	SC/APC







SECONDARY SPLITTER FOR UNIFIED ROE



The PLC (Planar Lightwave Circuit) is a type of optical splitter which uses planar technology and provides low insertion loss, uniformly dividing the optical signal from an input fiber in two or more output fibers. These non-wavelength selective optical splitting devices are supplied with a plastic case specifically designed for UNIFIED ROE, it has pre-installed SC/APC adapter both for input and output and it is precabled internally.



PRODUCT CODE

PLC-1X8-A-09/XX-SCA-09/XX-SCA-ROEU / Splitter pre-cabled 1x8 for UNIFIED ROE - NMU 776702

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
SPLITTING LEVEL	1x8
WORKING BANDWIDTH	1260 / 1650 nm
INSERTION LOSS MAX	10.7 dB
RETURN LOSS	55 dB
PDL (DB)	± 0.3 dB
FIBER DIAMETER	900 μm
ADAPTER TYPES	input SC/APC Simplex - output SC/APC Duplex
CASE TYPE	Plastico per Roe unificato
CASE SIZE	81x129x15,1 mm
CONNECTORS TYPE	SC/APC








CEX FILTER MODULE FOR FTTH



WDM CEx Filter module (Coeximstence Element) used in the optical monitoring of the FTTH network and for the distribution of services on PON architecture, which are described in the ITU-T recommendation G.984.5. These components allow the coexistence, on a single optical fiber, of G-PON, XG-PON, NG-PON2 systems together with the OTDR signal for monitoring the optical connection.



PRODUCT CODE

CWDM-1X4-SCA-100-M-T / CWDM module 1X4 with output: GPON, XG-PON, NG-PON2, OTDR. Input and output 0,9mm SC/APC connectorized, 1 m length, alluminum case

TECHNICAL FEATURES	
FIBER TYPE	G.657A1
WORKING BANDWIDTH	1260 ÷ 1675 nm
INSERTION LOSS MAX GPON	1.3 dB
INSERTION LOSS MAX XG-PON	1.6 dB
INSERTION LOSS MAX NG-PON2	1.7 dB
INSERTION LOSS MAX OTDR	1.9 dB
RETURN LOSS	50 dB
Insulation COM - GPON (dB) (1260-1280 nm; 1524-1675 nm)	35 dB
Insulation COM - XG-PON (dB) (1290-1560 nm; 1596-1675 nm)	35 dB
Insulation COM - NG-PON2 (dB) (1260-1500 nm; 1550-1581nm;	40 dB
1640- 1675 nm)	
Insulation COM - OTDR (dB)	10 db
PDL (DB)	0.2 dB
FIBER DIAMETER	0.9 mm
FIBER LENGHT	1000 mm
CASE TYPE	Alluminum case
CASE SIZE	60x50x7 mm
CONNECTORS TYPE	SC/APC







WDM MODULE PRE-INSTALLED IN FIST TYPE TRAY



Wave Division Multiplexing (WDM) is a technology that divides light into a number of discrete wavelengths or colors. Each wavelength / color is an independent channel capable of carrying independent shape and speed data. Typically, CWDM solutions provide capacity for 8 wavelengths, separated by 20nm, from 1470nm to 1610nm, allowing 8 customers interfaces to be carried on the same fiber.



PRODUCT CODE

F-OADM-C-1-47-0-2-0-L / 2-2×2 CWDM module (OADM) 1471NM, bare fiber 250μm not connectorized, fiber lenght 2M. F-OADM-C-1-51-0-2-0-L / 2-2×2 modulo CWDM (OADM) 1511NM, bare fiber 250μm not connectorized, fiber lenght 2M. F-OADM-C-1-53-0-2-0-L / 2-2×2 modulo CWDM (OADM) 1531NM, bare fiber 250μm not connectorized, fiber lenght 2M. F-OADM-C-1-49-0-2-0-L / 2-2×2 modulo CWDM (OADM) 1551NM, bare fiber 250μm not connectorized, fiber lenght 2M. F-OADM-C-1-49-0-2-0-L / 2-2×2 modulo CWDM (OADM) 1491NM, bare fiber 250μm not connectorized, fiber lenght 2M. F-OADM-C-1-59-0-2-0-L / 2-2×2 modulo CWDM (OADM) 1591NM, bare fiber 250μm not connectorized, fiber lenght 2M.

TECHNICAL FEATURES	
FIBER TYPE	G.657A2
CHANNELS	4
CHANNEL PASSING BANDWITH (NM)	1471±7.5 - 1511±7.5 - 1531±7.5
	1551±7.5 - 1491±7.5 - 1591±7.5
INSERTION LOSS MAX	0.7 dB
RETURN LOSS	Min 50 dB
PDL (DB)	Max 0,1 dB
RIPPLE	Max 0.3 dB
INSULATION	Min 30 dB
FIBER DIAMETER	250 μm
FIBER LENGHT	200 cm
CASE TYPE	Fist type splice tray
CASE SIZE	100x148x8 mm
CONNECTORS	Not connectorized







RFID



RFIDs are identifiers tags which can be applied to primary and secondary optical distribution network elements, both during the first installation phase and during maintenance on existing elements.













PRODUCT CODE

RFID-TAG-ABS/ RFID Tag for metallic components (rigid ABS support)

RFID-TAG-BOR/ RFID Tag for Open Fiber OTO (White PVC)

RFID-TAG-PL-PVC/ RFID Tag for plastic components

RFID-TAG-TR-FI-TH-SL / RFID Tag for mini-cables (with heath shrink)

RFID-TAG-TR-FI/ RFID Tag for mini-cable (with protective transparent label)

RFID-TAG-TR-FI-2 / RFID Tag for mini-cable (with protective transparent label) and rigid ABS support

TECHNICAL FEATURES	
MEMORY CAPACITY	1kb overwritable and lockable
TRANSMISSION FREQUENCY	13,5 MHz
RFID TYPE	Passive Tag A 14443
READING AND WRITING STANDARDS	NFC
DIMENSIONS	15x30x0,4 (PVC)








4 SLE FIST TYPE



The FIST type SLE splice trays can be installed inside optical subracks, in closures or in optical cabinets. They can house up to 12 splices, with standard type splice smouvs, allowing the correct management of the fiber extra lenght. The FIST-TRAY-KIT-4SLE-S item includes 4 trays with a 4 mm height, 1 pc tray cover and the 4-position holder (4 mm). The standard product is in gray color.



PRODUCT CODE

FIST-TRAY-KIT-4SLE-S / Kit made of: 4pcs grey splice trays (4mm) which can host 12 smouvs each, 1pc holder for 4 splice trays (4mm) and 1pc cover.

TECHNICAL FEATURES	
N. TRAYS	4
TRAYS THICKNESS	4 mm
N. OF SMOUVS	12
SMOUVS DIMENSION	Standard
TRAYS HOLDER	lt can host 4 trays (4mm)
COVER	1
MATERIAL	ABS
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







4 SC FIST TYPE



The FIST SC type splice trays can be positioned inside optical subracks, in closures or in optical patch cabinets. They can host up to 4 splices, with standard type splice smouvs, allowing the correct management of the fiber extra lenght. The FIST-TRAY-KIT-4SC-S item includes 4 pcs of 4 mm splice trays, 1 pc tray cover and the 4-position holder (4 mm). The standard product is in gray color.





PRODUCT CODE

FIST-TRAY-KIT-4SC-S / Kit made of: 4pcs grey splice trays (4mm) which can host 4 smouvs each, 1pc holder for 4 splice trays (4mm) and 1pc cover.

TECHNICAL FEATURES	
N. TRAYS	4
TRAYS THICKNESS	4 mm
N. OF SMOUVS	4
SMOUVS DIMENSION	Standard
TRAYS HOLDER	It can host 4 trays (4mm)
COVER	No
MATERIAL	ABS
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







8 SC FIST TYPE



The FIST type SC splice trays can be positioned inside optical subracks, in closures or in optical patch cabinets. They can host up to 4 splices, with standard type splice smouvs, allowing the correct management of the fiber extra lenght. The FIST-TRAY-KIT-8SC-S item includes n. 8 splice trays of 4 mm, 1 pc tray cover and the 8-position holder (4 mm). The standard product is in gray color.





PRODUCT CODE

FIST-TRAY-KIT-8SC-S / Kit made of: 8 pcs grey splice trays (4mm) which can host 4 smouvs each, 1pc holder for 8 splice trays (4mm) and 1pc cover.

TECHNICAL FEATURES	
N. TRAYS	8
TRAYS THICKNESS	4 mm
N. OF SMOUVS	4
SMOUVS DIMENSION	Standard
TRAYS HOLDER	lt can host 8 trays (4mm)
COVER	No
MATERIAL	ABS
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C








4 SE FIST TYPE



The FIST type SE splice trays can be positioned inside optical subracks, in closures or in optical patch cabinets. They can host up to 12 splices, with standard type splice smouvs, allowing the correct management of the fiber extra lenght. The FIST-TRAY-KIT-4SE item includes n. 4 splice trays of 8 mm, 1 pc tray cover and the 8-position holder (4 mm). The standard product is in gray color.



PRODUCT CODE

FIST-TRAY-KIT-4SE / Kit made of: 8 pcs grey splice trays (8mm) which can host 12 smouvs each, 1pc holder for 8 splice trays (4mm) and 1pc cover.

TECHNICAL FEATURES	
N. TRAYS	4
TRAYS THICKNESS	8 mm
N. OF SMOUVS	12
SMOUVS DIMENSION	Standard
TRAYS HOLDER	It can host 8 trays (8mm)
COVER	No
MATERIAL	ABS
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







2 COMPACT SE SPLITTER TRAYS



Compact splice trays for closures, optical patch cabinets or optical subracks. The 2SE-02SP-KIT-CLO item includes 2 pcs splice trays of 8 mm that can host up to 2 splitters each, allowing the correct management of the fiber extra lenght. The 4-position holder (4mm) with the ideal passages for closure applications is included and the product is supplied in gray color. The cover includes the pen for fiber handling, and it can be added with the code SE-SC-COVER-PEN. The tube entry for closure support, if necessary, can be ordered with the code TUBES-ENTRY-CLO.









PRODUCT CODE

2SE-02SP-KIT-CLO / Kit made of: 2 pcs grey splice trays (8mm) with 2 splitters space each and a 4-position closure-type support for 4mm trays

SE-SC-COVER-PEN / Cover + pen schede for SE and SC type trays

TECHNICAL FEATURES	
N. TRAYS	2
TRAYS THICKNESS	8 mm
N. OF SPLITTERS	2
SPLITTER CASE DIMENSION	1 (4x4x40mm) + 1 (4x7x60mm)
TRAY HOLDER	lt can host 2 trays (8mm)
COVER	No
MATERIAL	ABS + PC
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







2 COMPACT SE FOR 12 MICRO-SMOUV



Compact splice trays for closures, optical patch cabinets or optical subracks. The 2SE-12FO-KIT-CLO item includes 2 pcs splice trays of 8 mm that can host up to 12 micro-smouv splices each, allowing a correct management of the fiber extra lenght. The 4-position support (4mm) with the ideal passages for closure applications is included and the product is supplied in gray color. The cover includes the pen for fiber handling, and it can be added with the code SE-SC-COVER-PEN. The tube entry for closure support, if necessary, can be ordered with the code TUBES-ENTRY-CLO.









PRODUCT CODE

2SE-12FO-KIT-CLO / Kit made of: 2 pcs grey splice trays (8mm) with 12 micro-smouvs space each and a 4-position closure-type support for 4mm trays

SE-SC-COVER-PEN / Cover + pen schede for SE and SC type trays

TECHNICAL FEATURES	
N. TRAYS	2
TRAYS THICKNESS	8 mm
N. OF SMOUVS	12
SMOUVS DIMENSION	Tipo Micro
TRAY HOLDER	Da 4 posizioni per schede di giunzione da 4 mm per muffola
COVER	No
MATERIALE	ABS + PC
COLORE	Grigio
OPERATING TEMPERATURE	-40 ÷+70 °C







2 COMPACT SE TRAYS FOR 24 MICRO-SMOUV



Compact splice trays for closures, optical patch cabinets or optical subracks. The 2SE-24FO-KIT-CLO item includes 2 pcs splice trays of 8 mm that can host up to 24 micro-smouv splices each, allowing a correct management of the fiber extra lenght. The 4-position support (4mm) with the ideal passages for closure applications is included and the product is supplied in gray color.

The cover includes the pen for fiber handling, and it can be added with the code SE-SC-COVER-PEN. The tube entry for closure support, if necessary, can be ordered with the code TUBES-ENTRY-CLO.









PRODUCT CODE

2SE-24FO-KIT-CLO / Kit made of: 2 pcs grey splice trays (8mm) with 24 micro-smouvs space each and a 4-position closure-type support for 4mm trays

SE-SC-COVER-PEN / Cover + pen schede for SE and SC type trays

TECHNICAL FEATURES	
N. TRAYS	2
TRAYS THICKNESS	8 mm
N. OF SMOUVS	24
SMOUVS DIMENSION	Micro-smouv type
TRAY HOLDER	lt can host 2 trays (8mm)
COVER	No
MATERIAL	ABS + PC
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







4 COMPACT SC TRAYS FOR 6 MICRO-SMOUV



Compact splice trays used in closures, in optical patch cabinets or optical subracks. The item 4SC-06FO-KIT-CLO includes 4 pcs splice trays of 4 mm which can host up to 6 micro-smouv splices each, allows a correct management of the fiber extra lenght. The 4-position holder (4 mm) with the ideal passages for closure applications is included and the product is supplied in gray color. The cover includes the pen for fiber handling, can be added with the code SE-SC-COVER-PEN. The tube entry for closure support, if necessary, can be ordered with the code TUBES-ENTRY-CLO.









PRODUCT CODE

4SC-06FO-KIT-CLO / Kit made of: 4 pcs grey splice trays (4mm) with 6 micro-smouvs space each and a 4-position closure-type support for 4mm trays

SE-SC-COVER-PEN / Cover + pen schede for SE and SC type trays

TECHNICAL FEATURES	
N. TRAYS	4
TRAYS THICKNESS	4 mm
N. OF SMOUVS	6
SMOUVS DIMENSION	Tipo Micro
TRAY HOLDER	lt can host 4 trays (4mm)
COVER	NO
MATERIAL	ABS + PC
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C







4 COMPACT SC TRAYS FOR 12 MICRO-SMOUV



Compact splice trays used in closures, in optical patch cabinets or optical subracks. The 4SC-12FO-KIT-CLO item includes 4 pcs of 4mm splice trays that can host up to 12 micro-smouv splices each, allowing for proper management of the fiber extra lenght. The 4-position (4mm) holder with the ideal passages for closure applications is included and the product is supplied in gray color. The cover includes the pen for fiber handling, can be added with the code SE-SC-COVER-PEN. The tube entry for closure support, if necessary, can be ordered with the code TUBES-ENTRY-CLO.









PRODUCT CODE

4SE-12FO-KIT-CLO / Kit made of: 4 pcs grey splice trays (4mm) with 12 micro-smouvs space each and a 4-position closure-type support for 4mm trays

SE-SC-COVER-PEN / Cover + pen schede for SE and SC type trays

TECHNICAL FEATURES	
N. TRAYS	4
TRAYS THICKNESS	4 mm
N. OF SMOUVS	12
SMOUVS DIMENSION	Micro type
TRAY HOLDER	lt can host 4 trays (4mm)
COVER	No
MATERIAL	ABS + PC
COLOR	Grey
OPERATING TEMPERATURE	-40 /+70 °C











I FTTH - FTTR



FIBER TO THE HOME



The FTTH (Fiber To The Home) network is the one that allows the direct arrival of fiber optic cables to your home, greatly improving the performance of your Internet connection compared to previous copper connections. In this case, the speed can reach up to 1,000 Megabits per second (both in upload and download).

The chosen technology upstream for the FTTH structure is called GPON (Gigabit Passive Optical Network).

With GPON technology, which uses glass fiber to transmit light signals, it is possible to transmit and receive very large quantities of data over long distances without any 'active' network components, with great scalability and reduced maintenance.

OUT LINE has been developing projects and providing products for the installation of the fiber optic network throughout Italy and other countries for years. Furthermore, thanks to its Research and Development department, it has become a point of reference for the largest operators in the TLC sector. Although continuously developing, OUT LINE's offer for FTTH can be divided as follows:

FTTH in-Building products

When inside the building, it is needed a complete kit with all the components necessary to reach each flat and serve the users. OUT LINE offers a complete portfolio of products that allows each operator to carry out the complete cabling.

FTTH connection products

OUT LINE can supply a complete range of metal/plastic boxes, usually installed on the façade or inside buildings, for the connection and management of fiber optical cables coming from the manholes installed on the street.


Wide range of fiber optical components

OUT LINE has been supplying for several years most of the optical components and accessories needed for the deployment of the network infrastructure: Splitters, Pigtails, Connectors, Reflectors and much more.









PRIMARY FLOOR DIVIDER



The Primary floor divider is a product designed and developed to allow the protection and separation of single fibers and fiber groups that are extracted from a vertical multi-fiber drop cable installed in the building.



PRODUCT CODE

VERT-DIR-PRINC/ Primary Floor Divider (30 pcs pack)

TECHNICAL FEATURES	
MATERIAL	ABS
HEIGHT	26 mm
LENGHT	86 mm
DEPTH	86 mm
COLOR	White
FLAME RESISTANCE	UL94-V0
INPUT	N. 1 passing cable up to 9 mm diameter
OUTPUT FOR 3 MM PROTECTIVE TUBES	12
OUTPUT FOR 5 MM PROTECTIVE TUBES	2
GUARANTEED BENDING RADIO	15 mm







SECONDARY FLOOR DIVIDER



The Secondary floor divider is a product designed and developed to allow the protection and separation of single fibers and groups of fibers coming from the main branch or multi-fibers drop cables to be terminated directly with a branch on the floor.



PRODUCT CODE

VERT-DIR-SECON/ Secondary Floor Divider (30 pcs pack)

TECHNICAL FEATURES	
MATERIAL	ABS
DEPTH	10 mm
DIAMETER	40 mm
COLOR	White - RAL 9016
TUBES/CABLES ENTRANCES	1pc up to 5 mm diameter
OUTPUTS FOR 3 MM PROTECTIVE TUBES	8
OUTPUTS FOR 5 MM PROTECTIVE TUBES	3
GUARANTEED BENDING RADIO	15 mm
FLAME RESISTANCE	UL94-V0







MINI FLOOR-BOX



The Mini floor-box allows the extraction and splicing on each floor of the optical fibers, which are used for the cabling of the individual flats, from the vertical multifiber drop cable installed in the building.



PRODUCT CODE

VERT-BOX-PIANO / Mini floor-box (30 pcs pack)

TECHNICAL FEATURES	
MATERIAL	ABS
HEIGHT	26 mm
LENGHT	70 mm
DEPTH	50 mm
COLOR	White - RAL 9016
FLAME RESISTANCE	UL94-V0
PASSING CABLE ENTRANCES	N. 1 passing cable up to 9 mm diameter
CABLE'S OUTPUT	12
GUARANTEED BENDING RADIO	15 mm
RAGGIO DI CURVATURA GARANTITO	15 mm








PROTECTIVE TUBE



The PE protective tube is needed for the protection of single fibers or groups of fibers and is mainly used for the passage between the various types of branchers and the end customer's apartment. The protective tube for multiple fibers can be used to protect the fibers that come from the cable dividers in the ODF or subracks.





PRODUCT CODE

VERT-TUB-SING/ Protective tube for single fiber (500mt drum) **VERT-TUB-MULTI/** Protective tube for multiple fibers (500mt drum)

TECHNICAL FEATURES		
	Single Fiber Multiple Fibers	
EXTERNAL DIAMETER	3 mm 5 mm	
INTERNAL DIAMETER	1.4 mm 3.5 mm	
WORKING TEMPERATURE	-15 / +70 ° C	
MINIMUM BENDING RADIUS	15 mm 20 mm	
COLOR	Trasparent	







SPLICE PROTECTION SYSTEM



The splice protection system consists in a plastic tube that is used after the branching of a multi-fiber cable for the splice protection. This is used inside a corrugated tube between a fiber of the multi-fiber cable in the building and the fiber of the single-fiber cable that carries the connection to the end user's flat.



PRODUCT CODE

VERT-TUB-SMV/ Splice protection system (100 pcs pack)

TECHNICAL FEATURES		
EXTERNAL DIAMETER	5 mm	
INTERNAL DIAMETER	3,5 mm	
TUBE LENGHT	400 mm	
HEATH-SHRINKABLE LENGHT	30 mm	
COLOR	Trasparent	
TUBE MATERIAL	PE	
RING MATERIAL	Brass	
FLAME RESISTANCE	UL94V0	







PLESIO - UNI 503



THE PLESIO - UNI 503 has been developed for Italy market, because it is meant to be mounted above an UNI 503 electrical socket box. It is made in a rectangular geometric structure, which follows the perimeter of a standard UNI 503 box. It is equipped with a front cover which has a central break set, once the set is broken the cover can be installed on a UNI 503 box even in the presence of pre-installed electrical sockets. It allows the fixing of the single-fiber cable with 5 entry options, it provides a fiber extra-lenght management zone with a 900um jacket, it can host standard fusion splice covers in two opposite positions to offer greater flexibility. It also contains n. 1 SC/APC adapter but it can also host shutter type SC/APC adapters. It is possible to install mechanical connectors, Splice-on connectors and optical reflectors inside it.





PRODUCT CODE

WO-1F-CORN

TECHNICAL FEATURES		
MATERIAL	ABS	
HEIGHT	86 mm	
LENGHT	122 mm	
DEPTH	16 mm	
COLOR	White	
ADAPTER TYPE	SC/APC	
COPPER CONNECTION	RJ11 (OPTIONAL)	
ADAPTER	SC/APC Flangeless	







OPEN FIBER OTO



This user optical socket developed and homologated by Open Fiber, allows the connection of individual apartments to the vertical access fiber optic network. Small and aesthetically pleasing, the termination inside the socket can be achieved via a 900 μ m pigtail with SC/APC Splice-on Connector, or with a field-installable SC/APC connector. It can easily host a monodirectional FBG optical reflector. Standard configuration includes an SC/APC shutter adapter.





PRODUCT CODE

WO-1F-SH-OF

TECHNICAL FEATURES	
N. OF ADAPTERS	1
ADAPTER TYPE	SC/APC Simplex
MATERIAL	ABS
COLOR	WHITE
HEIGHT	22 mm
WIDTH	85 mm
DEPTH	115 mm








HYBRID (COPPER / FIBER) OTO



The Unified User Termination with hybrid connectivity has been developed and homolgated for a TELECOM ITALIA technical specification, and allows the connection of individual apartments to the vertical access fiber optic network installed in buildings. Small and aesthetically pleasing, it gives an hybrid solution: it includes n. 1 SC/APC adapter, n. 1 RJ11 and n. 1 RJ25 already installed on an electronic card. The RJ connectors are used to restart the phone copper network existing in the apartment.





PRODUCT CODE

WO-IFO/ N.M.U. TIM 767653

TECHNICAL FEATURES		
MATERIAL	ABS	
HEIGHT	28 mm	
WIDTH	80 mm	
DEPTH	80 mm	
COLOR	White	
OPTICAL CONNECTION	SC/APC	
COPPER CONNECTION	RJ11 + RJ25	
ADAPTER	SC/APC with flanges	







VDSL2 (CBS) SOCKET



The VDSL2 or CBS user socket has the fundamental characteristic of recovering the system at the customer premises, in response to the activation of an FTTCab/VDSL2 service offer. The VDSL2 User Socket allows connections on the Customer side made using RJ11 and RJ25 connectors, while on the Central side and internal system side with IDC type connectors





PRODUCT CODE

WO-CBS-WDSL2/ NMU 776610

TECHNICAL FEATURES	
MATERIAL	ABS
HEIGHT	55 mm
WIDTH	75 mm
DEPTH	35 mm
COLOR	White
COPPER CONNECTION	RJ11 + RJ25







OPTILINK - REEL WALL OUTLET



Fiber wall outlet with a 10/20/30/40 meters SC/LC-APC patch cord connected to an adapter. The patch cord is coiled up inside the outlet on a rotating spool that allows it to be stored inside the outlet as well as unwound to the outside. Optilink can be used to bring a fiber optic Internet connection to any room in the house, thanks to its cable that can be extended up to 40 meters.





PRODUCT CODE

CODE BASED ON OPTIONS - ASK US A QUOTATION BASED ON YOUR NEEDS

TECHNICAL FEATURES		
MATERIAL	ABS	
HEIGHT	80 mm	
WIDTH	80 mm	
DEPTH	28,5 mm	
COLOR	RAL 9016	
FLAMABILITY GRADE	UL94 VO	








PLESIO - DIN



This user optic socket has been developed to allow the connection of the individual home apartments to the FTTH fiber optic network. Small and aesthetically pleasing, the termination inside the box can accommodate up to 2pcs 900 μ m pigtail with SC/APC (or LC/APC) connector that can be spliced to the optical cable, or with fast SC/APC (or LC/APC) mechanical connector.





PRODUCT CODE

CODE BASED ON OPTIONS - ASK US A QUOTATION BASED ON YOUR NEEDS

TECHNICAL FEATURES		
MATERIAL	ABS	
HEIGHT	101 mm	
WIDTH	101 mm	
DEPTH	16,5 mm	
COLOR	White	
OPTICAL CONNECTION	SC/APC - LC/APC	
ADAPTER	SC/APC - LC/APC	
FLAMABILITY GRADE	UL94 VO	







4 FO OTO



This user optical socket allows the connection of individual apartments to the vertical access fiber optic network. Small and aesthetically pleasing, the termination inside the socket can be achieved via a 900 μ m pigtail with SC/APC Splice-on Connector, or with a field-installable SC/APC connector. It can easily host up to 4 fibers.





PRODUCT CODE

WO-4F/ 4 FO OTO

TECHNICAL FEATURES	
N. OF ADAPTERS	4
ADAPTER TYPE	SC/APC Simplex
MATERIAL	ABS
COLOR	White
HEIGHT	28,8 mm
WIDTH	100,6 mm
DEPTH	80,6 mm















SILVAY® BRINGS FIBER EVERYWHERE

With SILWAY you can bring the optical fiber and the modem to any point of your

home or office.

Where it is not possible to use the existing electrical system ducts, the system allows you to lay the cables in a simple and clean way without any particular masonry work.

The SILWAY system creates a protective path dedicated to the cables, including the optical fiber up to 2.5 mm outer diameter, overcoming the clogging of junction boxes and corrugated pipes that often hinder the passage of such delicate cables.















Each KIT includes 50m of SILWAY duct, and:



Inner Curve Accessory



Fiber-Placing Tool



External Curve Accessory



WPT / Divider Accessory



Planar Curve Accessory



Protective Tube











ROE - 8 HH



ROE 8 HH is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 1 pc of 1x8 PLC splitter (OL code: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).



PRODUCT CODE

ROE-8-TIM-NL / ROE (NMU 771782) includes n. 1 SC/APC SIMPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES		
HEIGHT	150 mm	
LENGHT	114 mm	
DEPTH	60 mm	
TERMINATION (HORIZONTAL BRANCH)	Up to 2 SC/APC Simplex	
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Simplex	
CABLE ENTRANCES	3	
PROTECTION CLASSIFICATION	IP56 - IK10	
MATERIAL	ABS	
COLOR	RAL 7035	
LOCK	-	
PARKING	1	







ROE 16 HH



ROE 16 HH is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 2 pc of 1x8 PLC splitter (OL code: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).



PRODUCT CODE

ROE-16-TIM-FF/ ROE 16 HH (NMU 771783) includes n. 6 SC/APC SIMPLEX adapter pre-installed in the secondary branch and n. 16 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES		
HEIGHT	250 mm	
LENGHT	150 mm	
DEPTH	70 mm	
TERMINATION (HORIZONTAL BRANCH)	Up to 6 SC/APC Simplex	
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Duplex	
CABLE ENTRANCES	3	
PROTECTION CLASSIFICATION	IP56 - IK10	
MATERIAL	ABS	
COLOR	Color RAL 7035	
LOCK	-	
PARKNG	4	







ROE 16 HH - INTERNAL FRUIT



ROE 16 HH – INTERNAL FRUIT is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 2 pc of 1x8 PLC splitter (OL code: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).





PRODUCT CODE

ROE-16-TIM-COL-FF / ROE 16 HH INTERNAL FRUIT (NMU 771785) includes n. 6 SC/APC SIMPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	250 mm
LENGHT	150 mm
DEPTH	70 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 6 SC/APC Simplex
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Duplex
CABLE ENTRANCES	3
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS
COLOR	Color RAL 7035
LOCK	-
PARKING	4








ROE 32 HH



ROE 32 HH is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 4 pc of 1x8 PLC splitter (OL code: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).





PRODUCT CODE

ROE-32-TIM-FF / ROE 32 HH (NMU 771784) includes n. 12 SC/APC SIMPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	300 mm
LENGHT	300 mm
DEPTH	120 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 12 SC/APC SIMPLEX
TERMINATION (USER'S BRANCH)	Up to 16 SC/APC DUPLEX
CABLE ENTRANCES	5
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS
COLOR	Color RAL 7035
LOCK	UPON REQUEST
PARKING	8







ROE 32 HH - INTERNAL FRUIT



ROE 32 HH is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 4 pc of 1x8 PLC splitter (OL code: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).





PRODUCT CODE

ROE-32-TIM-COL-FF / ROE 32 HH INTERNAL FRUIT (NMU 771787) includes n. 12 SC/APC SIMPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	300 mm
LENGHT	300 mm
DEPTH	120 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 12 SC/APC SIMPLEX
TERMINATION (USER'S BRANCH)	Up to 16 SC/APC DUPLEX
CABLE ENTRANCES	5
PROTECTION CLASSIFICATION	ABS
MATERIAL	Color RAL 7035
COLOR	-
PARKING	8







ROE 48 HH



ROE 48 HH is designed for pole or wall installations and is used for Fiber To The Home applications. It can host n. 6 PLC splitter 1x8 (OL CODE: PLC-1X8-A-09/105-SCA-09/095-SCA-2), and the incoming cable is divided inside the ODB and then distributed to the individual House-Holds (HH).



PRODUCT CODE

ROE-48-UI-PRY /ROE 48 HH MTCV (NMU 767700) **ROE-48-UI-TEL** / DIN RAIL KIT for ROE 48 HH (NMU 767701)

TECHNICAL FEATURES	
HEIGHT	180 mm
LENGHT	450 mm
DEPTH	150 mm
TERMINATION (HORIZONTAL BRANCH)	Fino a 6 SC/APC Simplex
TERMINATION (USER'S BRANCH)	Fino a 48 SC/APC simplex'
CABLE ENTRANCES	4
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	METALLO
COLOR	Colore RAL 7035
LOCK	Sicurvite
PARKING	12








ROE UNI 16 HH



The ROE UNI 16 HH is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network, it hosts 1X8 plastic splitters (OL CODE: PLC-1X8-A-09/XX-SCA-09/XX-SCA-ROEU). It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field. Furthermore, the external case can be replaced in the event of damage, without any service interruption.



PRODUCT CODE

ROE-16-UNI-IE-OL-TIM / ROE UNI 16 HH (NMU 777328) includes n. 2 SC/APC DUPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	288 mm
LENGHT	215 mm
DEPTH	108 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 2 SC/APC Duplex
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Simplex
CABLE ENTRANCES	4
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	Sicurvite TYPE








ROE UNI 16 HH - INTERNAL FRUIT



The ROE UNI 16 HH – INTERNAL FRUIT is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network, it hosts 1X8 plastic splitters (OL CODE: PLC-1X8-A-09/XX-SCA-09/XX-SCA-ROEU). It can be easily assembled/cabled with more comfort in the field but it must be installed in a bigger box or cabinet.





PRODUCT CODE

ROE-16-UNI-COL-OL-TIM / ROE UNI 16 HH – INTERNAL FRUIT (NMU 777375) includes n. 2 SC/APC DUPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	288 mm
LENGHT	215 mm
DEPTH	108 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 2 SC/APC Duplex
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Simplex
CABLE ENTRANCES	4
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	-







PTE UNI 24 HH



PTE UNI 24 HH is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network. It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field. Furthermore, the external case can be replaced in the event of damage, without any service interruption.





PRODUCT CODE

PTE-24-UNI-IE-OL-TIM / PTE UNI 24 HH (NMU 777390) includes n. 24 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	288 mm
LENGHT	215 mm
DEPTH	108 mm
TERMINATION (USER'S BRANCH)	Up to 24 SC/APC Simplex
CABLE ENTRANCES	4
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	Sicurvite TYPE







PTE UNI 24 HH - INTERNAL FRUIT



PTE UNI 24 HH – INTERNAL FRUIT is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network. It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field but it must be installed in a bigger box or cabinet.





PRODUCT CODE

PTE-24-UNI-COL-OL-TIM / PTE UNI 24 HH – INTERNAL FRUIT (NMU 777392) includes n. 24 SC/APC SIMPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	255 mm
LENGHT	182 mm
DEPTH	87 mm
TERMINATION (USER'S BRANCH)	Up to 24 SC/APC Simplex
CABLE ENTRANCES	4
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	-







ROE UNI 32 HH



The ROE UNI 32 HH is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network, it hosts 1X8 plastic splitters (OL CODE: PLC-1X8-A-09/XX-SCA-09/XX-SCA-ROEU). It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field. Furthermore, the external case can be replaced in the event of damage, without any service interruption.





PRODUCT CODE

ROE-32-UNI-IE-OL-TIM / ROE UNI 32 HH (NMU 777327) includes n. 4 SC/APC DUPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	360 mm
LENGHT	260 mm
DEPTH	133 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 4 SC/APC Duplex
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Duplex
CABLE ENTRANCES	3
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	Sicurvite TYPE








ROE UNI 32 HH - INTERNAL FRUIT



The ROE UNI 32 HH – INTERNAL FRUIT is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network, it hosts 1X8 plastic splitters (OL CODE: PLC-1X8-A-09/XX-SCA-09/XX-SCA-ROEU). It can be easily assembled/cabled with more comfort in the field but it must be installed in a bigger box or cabinet.





PRODUCT CODE

ROE-32-UNI-COL-OL-TIM / ROE 32 HH – INTERNAL FRUIT (NMU 777329) includes n. 4 SC/APC DUPLEX adapter pre-installed in the secondary branch and n. 8 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	328 mm
LENGHT	220 mm
DEPTH	140 mm
TERMINATION (HORIZONTAL BRANCH)	Up to 4 SC/APC Duplex
TERMINATION (USER'S BRANCH)	Up to 8 SC/APC Duplex
CABLE ENTRANCES	6
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	-







PTE UNI 48 HH



PTE UNI 48 HH is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network. It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field. Furthermore, the external case can be replaced in the event of damage, without any service interruption.





PRODUCT CODE

80

PTE-48-UNI-IE-OL-TIM / PTE UNI 48 HH (NMU 777376) includes n. 24 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	360 mm
LENGHT	260 mm
DEPTH	133 mm
TERMINATION (USER'S BRANCH)	Up to 24 SC/APC Duplex
CABLE ENTRANCES	6
PROTECTION CLASSIFICATION	IP56 - IK10
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	Sicurvite TYPE







PTE UNI 48 HH - INTERNAL FRUIT



PTE UNI 48 HH – INTERNAL FRUIT is designed for internal and external installation, for the cabling of buildings part of a FTTH architecture network. It has a back-panel appropriately designed so that it can be dismounted and easily assembled/cabled with more comfort in the field but it must be installed in a bigger box or cabinet.





PRODUCT CODE

PTE-48-UNI-COL-OL-TIM /PTE 48 HH – INTERNAL FRUIT (NMU 777391) includes n. 24 SC/APC DUPLEX adapters pre-installed in the user's branch.

TECHNICAL FEATURES	
HEIGHT	328 mm
LENGHT	240 mm
DEPTH	114 mm
TERMINATION (USER'S BRANCH)	Up to 24 SC/APC Duplex
CABLE ENTRANCES	6
MATERIAL	ABS/PC
COLOR	Color RAL 7035
LOCK	-








PTE 8/16/24 HH



PTE 8/16/24 HH represent the termination point of the optical fibers coming from the primary network, inside or outside the Customer's buildings with the possibility of being mounted on a pole. The structure is composed of three compartments: the lower base; the removable internal part (so called 'fruit') with cable entries, locking systems and splice trays; the tilting module which hosts an adapter branch for up to 24 positions for SC type connectors and the extra length management area for network cables. Furthermore, on the front part of the internal fruit there is an extra length management area also for branch cables or riser cables.





PRODUCT CODE

PTE-24UI-08AD/ PTE 8 HH includes n. 8 SC/APC SIMPLEX adapters in the user's branch. **PTE-24UI-16AD/** PTE 16 HH includes n. 16 SC/APC SIMPLEX adapters in the user's branch. **PTE-24UI-24AD/** PTE 24 HH includes n. 24 SC/APC SIMPLEX adapters in the user's branch.

TECHNICAL FEATURES	
ADAPTER TYPE	SC Simplex (or LC Duplex upon request)
HEIGHT	235 mm
LENGHT	145 mm
DEPTH	90 mm
MAX NUMBER OF POSITIONS	24
CABLE ENTRANCES	6
NUMBER OF OUTPUTS	2
PROTECTION CLASSIFICATION	IP65 - IK09
MATERIAL	ABS
COLOR	Grigio
WORKING TEMPERATURES	40 / +70 °C







12 USERS



The RDB-12E optical box can manage up to 12 SC fibers, it can in fact host 12 Simplex SC Adapters, it has a space set up for housing 1 splitter. Below the trays there is the area for splicing the single fibres and a space for any management of the extra lenghts.



PRODUCT CODE

RDB-12E/ Up to 12 SC fibers connections

TECHNICAL FEATURES	
ADAPTER TYPE	SC Simplex / LC Duplex
N. OF POSITIONS	12
CABLES INPUTS	4
USERS EXITS	16
OPERATING TEMPERATURE	-40 / +60 °C
PLC SPLITTER	1x4/8
HEIGHT	82 mm
WIDTH	175 mm
DEPTH	274 mm
MATERIAL	ABS
COLOR	Grey
PROTECTION CLASS	IP65







ODB 24 HH



The RDB-24N optical box can manage up to 24 SC fibers, it can in fact host 24 Simplex SC Adapters, it has a space set up for housing up to 4 PLC splitters. Below the trays there is the area for splicing the single fibres and a space for any management of the extra lenghts.



PRODUCT CODE

RDB-24N / Up to 24 SC fibers

TECHNICAL FEATURES	
Up to 24 SC fibers	SC Simplex – LC Duplex
NUMERO DI POSIZIONI	24
NUMERO INGRESSI CAVI	4
NUMERO USCITE UTENTE	24
TEMPERATURA OPERATIVA	40 / +60 °C
PLC SPLITTER	4
ALTEZZA	87 mm
LARGHEZZA	210 mm
PROFONDITÀ	330 mm
MATERIALE	ABS
COLORE	Grey
PROTEZIONE	IP65








OPTICAL BOX

ODB 48 HH



The optical box RDB-48 can manage up to 48 SC fibers, it can in fact host 48 Simplex SC Adapters, it has a space set up for housing up to 4 PLC splitters. Below the trays there is the area for splicing the single fibres and a space for any management of the extra lenghts.



PRODUCT CODE

RDB-48 / Up to 48 SC fibers

TECHNICAL FEATURES	
ADAPTER TYPE	SC Simplex – LC Duplex
N. OF POSITIONS	48
CABLES INPUTS	4
USERS EXITS	2
OPERATING TEMPERATURE	40 / +60 °C
PLC SPLITTER	4
HEIGHT	114 mm
WIDTH	330 mm
DEPTH	350 mm
MATERIAL	ABS
COLOR	Light Grey
PROTECTION CLASS	IP65







OPTICAL BOX DIN FIXING



The optical box with DIN fixing point has a metal case which can insure an high resistance in critical environments, it can manage 12 Optical fibers on a frontal plate which can host 6 SC/SC duplex positions. It can be used with 1 passing cable input/out or 2 cable Input/out 45° angled.





PRODUCT CODE

DIN-M003/12C/SCD / MMETAL 12FO SC DUPLEX DIN fixing box

TECHNICAL FEATURES	
HEIGHT	130 MM
WIDTH	125 MM
DEPTH	34 MM
MATERIAL	Stainless Steel
CABLES INPUT/OUTPUT	2 A 45° / 1 PASSING
MAXIMUM CAPACITY	12 FO
HOSTABLE SMOUVS	Standard Smouvs
SMOUV DIMENSIONS	Ø 2,5 MM
FRONT PLATE	6 SC DUPLEX
COLOR	Color RAL 7035







OPTICAL BOX DIN FIXING



The optical box with DIN fixing point has a metal case which can insure an high resistance in critical environments, it can manage 12 Optical fibers on a frontal plate which can host 12 SC/SC simplex positions. It can be used with 1 passing cable input/output or 2 cable Input/ouput 45° angled.





PRODUCT CODE

DIN-M004/12C/SCD / METAL 12FO SC SIMPLEX DIN fixing box

TECHNICAL FEATURES	
HEIGHT	130 MM
WIDTH	125 MM
DEPTH	34 MM
MATERIAL	Stainless Steel
CABLES INPUT/OUTPUT	2 A 45° / 1 PASSING
MAXIMUM CAPACITY	12 FO
HOSTABLE SMOUVS	Standard Smouvs
SMOUV DIMENSIONS	Ø 2,5 MM
FRONT PLATE	12 SC SIMPLEX
COLOR	Color RAL 7035







OPTICAL BOX DIN FIXING



The plastic optical box with DIN fixing point allows to manage 12 SC-SC simplex adapters, The internal tray allows an inversion of fiber cables and on the base there are 2 input/output for multi-fiber cable termination or the blocking of a passing fiber cable.





PRODUCT CODE

DIN-P001/12C/SCD / PLASTIC 12FO SC SIMPLEX DIN fixing box

TECHNICAL FEATURES	
HEIGHT	133 mm
WIDTH	130 MM
DEPTH	35 MM
MATERIAL	Stainless Steel
CABLES INPUT/OUTPUT	2 / 1 PASSING
MAXIMUM CAPACITY	12 FO
HOSTABLE SMOUVS	Standard smouvs
SMOUV DIMENSIONS	Ø 2,5 MM
FRONT PLATE	12 SC Simplex
COLOR	Color RAL 7035











FIBER OPTIC CLOSURES



OPTICAL CLOSURE

SPLICES / 3+1 INPUT



The compact 48-junction, with 3 round inlet and 1 oval inlet, optical closure is a passive and watertight F.O. box, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantee a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and a pole or wall anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-03 / OPTICAL CLOSURE up to 48 splices with 3 circular input and 1 oval input

TECHNICAL FEATURES		
OVAL INPUTS	1	
ROUND INPUTS	3	
OVERALL DIAMETER (INCLUDING CLAMP)	188	
OVERALL HEIGHT (INCLUDING BASE)	300	
OVAL INPUT DIAMETER FOR HEAT-SHRINKABLE APPLICATION	20	
ROUND INPUT DIAMETER FOR HEAT-SHRINKABLE	16	
APPLICATION		
SPLICE TRAYS	4	
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.	
MAX SPLICING CAPACITY	up to 48 F.O	







288-SPLICES / 6+1 INPUTS



The 288-SPLICES, 6-round input + 1-oval input FIST-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-FST-6 / OPTICAL CLOSURE tipo FIST fino a 288 giunzioni con 6 ingressi circolari ed un ingresso ovale

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	6
OVERALL DIAMETER (INCLUDING CLAMP)	298 mm
OVERALL HEIGHT (INCLUDING BASE)	504 mm
OVAL INPUT DIAMETER FOR HEAT-SHRINKABLE APPLICATION	For 2 cables 10-25 mm
ROUND INPUT DIAMETER FOR HEAT-SHRINKABLE	From 6 to 33 mm
APPLICATION	
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to 288 F.O.







288-SPLICES / 16+1 INPUTS



The 288-SPLICES, 16-round input + 1-oval input FIST-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.





PRODUCT CODE

Q-CL-FST-16 / FIST type up to 288 splices with 16 circular input and 1 oval input

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	16
OVERALL DIAMETER (INCLUDING CLAMP)	298 mm
OVERALL HEIGHT (INCLUDING BASE)	504 mm
OVAL INPUT CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 8 PCS 16MM ROUND	6-16 mm
INPUT	
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 8 PCS 21MM ROUND	6-21 mm
INPUT	
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to288 F.O.







OPTICAL CLOSURE

96-SPLICES / 8+1 INPUTS



The 96-SPLICES, 8-round input + 1-oval input FOSC-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-B-8-TrayA-4 / FOSC type up to 96 splices with 8 circular input and 1 oval input

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	8
OVERALL DIAMETER (INCLUDING CLAMP)	160 mm
OVERALL HEIGHT (INCLUDING BASE)	530 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE OVAL INPUT	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 8 PCS ROUND INPUT	7-10 mm
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to 96 F.O.







96-SPLICES / 4+1 INPUTS



The 96-SPLICES, 4-round input + 1-oval input FOSC-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-B-4-TrayB-4 / OPTICAL CLOSURE FOSC type up to 96 splices with 4 circular input and 1 oval input

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	4
OVERALL DIAMETER (INCLUDING CLAMP)	160 mm
OVERALL HEIGHT (INCLUDING BASE)	530 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE OVAL INPUT	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 4 PCS ROUND INPUT	7-18 mm
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to 96 F.O.







96-SPLICES / 4+1 INPUTS



The COMPACT 96-SPLICES, 4-round input + 1-oval input FOSC-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.





PRODUCT CODE

Q-CL-A-4-TrayS1-4 / OPTICAL CLOSURE COMPACT FOSC type up to 96 splices with 4 circular input and 1 oval input

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	4
OVERALL DIAMETER (INCLUDING CLAMP)	160 mm
OVERALL HEIGHT (INCLUDING BASE)	420 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE OVAL INPUT	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 4 PCS ROUND INPUT	7-18 mm
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to a 96 F.O.







96-SPLICES / 8+1 INPUTS



The COMPACT 96-SPLICES, 8-round input + 1-oval input FOSC-type OPTICAL CLOSURE is a watertight, passive F.O. BOX, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantees a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and pole or wal anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-A-8-TrayS1-4 / OPTICAL CLOSURE COMPACT FOSC type up to 96 splices with 8 circular input and 1 oval input

TECHNICAL FEATURES	
OVAL INPUTS	1
ROUND INPUTS	8
OVERALL DIAMETER (INCLUDING CLAMP)	160 mm
OVERALL HEIGHT (INCLUDING BASE)	420 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE OVAL INPUT	2 cables from 20 to 25 mm
CABLE DIAMETER RANGE FOR HEAT-SHRINKABLE APPLICATION ON THE N. 4 PCS ROUND INPUT	7-10 mm
SPLICE TRAYS	24
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	Up to 96 F.O.











I FIBER OPTIC OUTDOOR CABINET



CRO 128 FO



The 128 FO CRO has been developed for the outdoor infrastructure and it is configured for the termination of primary and secondary network cables. Even if the dimension of this cabinet is very small and compact, it still can host up to 128 HH (secondary network). It can host 1x2, 1x4 and 1x16 HGLX splitters.

It's external case, including door and roof, can be dismounted in case of damage without interrupting the connections inside.



PRODUCT CODE

MINICRO-FC-2020-V1

TECHNICAL FEATURES	
MATERIAL	EXTERNAL PARTS: SUS 304 sp 1,5 mm DOOR: SUS 304 sp 1,2 mm INTERNAL PARTS: SUS 430 sp 1,2 mm
EXTERNAL DIMENSIONS	1220x335x300mm (AxLxP)
COLOR	Cabinet: RAL7037 Dusty Grey Roof: RAL 3020 Traffic Red
ADAPTERS QTY	128 + 48 SC/APC (secondary network + primary network)
SPLICE TRAYS QTY	16 + 6 grey color (splicing + secondary network parking) 6 + 4 red color (splicing + primary network parking)
SPLITTER QTY	up to 8 secondary splitters 1:16 up to 8 primary splitters 1:2 or 1:4
LOCK TYPE	Handle with three-point locking system Lock with Sicurvite profile







CRO 384 FO



The 384 FO CRO has been developed for the outdoor infrastructure and it is configured for the termination of primary and secondary network cables.

Despite the compact dimension of this cabinet it can host up to 384 HH (secondary network). It can host 1x2, 1x4 and 1x16 HGLX splitters.



PRODUCT CODE

CRO 2023-V0

TECHNICAL FEATURES	
MATERIAL	EXTERNAL PARTS: SUS 304 sp 1,5 mm DOOR: SUS 304 sp 1,2 mm INTERNAL PARTS: SUS 430 sp 1,2 mm
EXTERNAL DIMENSIONS	1300x750x250mm (AxLxP)
PROTECTION DEGREE	IP55 & IK10
COLOR	Cabinet: RAL7037 Grigio Polvere Tetto: RAL 3020 Rosso Traffico
ADAPTERS QTY	384 + 64 SC/APC (secondary network + primary network)
SPLICE TRAYS QTY	48 + 24 grey color (splice + secondary network parking) 8 + 8 red color (splice + primary network parking)
SPLITTER QTY	Up to 24 secondary splitter 1:16 Up to 14 primary splitter primari (1:2 or 1:4)
LOCK TYPE	TIM special lock (Can be changed according to the request)







CRO 576 FO



The 576 FO CRO is configured for the termination of primary and secondary network cables and the execution of permutations between the two multiplication levels and the secondary network.

The cabinet is designed for the placement of optical branch devices: up to 21 primary optical splitters and up to 40 secondary optical splitters.

This cabinet has a secondary and primary network termination area, consisting of a panel with 704 (576+128) adapters, which can be opened up to 90° to perform testing and maintenance operations.

The maximum estimated length required for the patchcords is 2,5 m. The maximum estimated length required for the secondary splitter input is 1,5 m.

The cabinet is equipped with 128 splice trays for the splicing and parking of the FO and each tray can accommodate up to 12 splices.



PRODUCT CODE

576CRO-FC-2025-V0

TECHNICAL FEATURES	
MATERIAL	EXTERNAL PARTS: SUS 304 sp 1,5 mm DOOR: SUS 304 sp 1,2 mm INTERNAL PARTS: SUS 430 sp 1,2 mm
EXTERNAL DIMENSIONS	1600x900x300mm (AxLxP)
COLOR	Cabinet: RAL7037 Dusty Grey Roof: RAL 3020 Traffic Red
LOCK TYPE	Handle with three-point locking system Lock with Sicurvite profile
ADAPTERS QTY	576 SC/APC secondary network 128 SC/APC primary network
SPLICE TRAYS QTY	72 secondary network (gray color) 24 primary network (red color)
PARKING TRAYS QTY	24 secondary network (gray color) 8 primary network (red color)
SPLITTER QTY	up to 40 secondary splitters 1:16 up to 21 primary splitters 1:2 or 1:4







CNO



The CNO cabinet allows, on a multioperator passive network (PON) that supports point-to-point and pointmultipoint technologies, the optical connection of up to 256 HH (secondary network), with the possibility of swapping, between the cables coming from a primary concentration element and the cables directed to the individual HH.

It's external case, including door and roof, can be dismounted in case of damage without interrupting the connections inside.



PRODUCT CODE

LNIT-CNO-INFRATEL

TECHNICAL FEATURES	Acciaio INOX AISI 304 per l'involucro esterno e in acciaio inossidabile AISI 430 o superio-
MATERIAL	re per le parti interne.
EXTERNAL DIMENSIONS	1100x700x200 mm (AxLxP)
COLOR	STANDARD RAL 7035
ADAPTERS QTY	256 + 24 SC/APC (rete secondaria + rete primaria)
SPLICE TRAYS QTY	Splicing/parking area of optical fibers connected to the cabinet, consisting of: - no. 22 SE trays for secondary network fiber splices, gray color; - no. 20 SF trays for secondary network fiber splices, gray color; - no. 2 SE trays for primary network fiber splices GPON, red color. - no. 5 SE trays for point-to-point network fiber splices, blue color; - no. 3 SF trays for primary network fiber splices, yellow color;
SPLITTER QTY	No. 1 optical splitter type 1:16 BUTT, fully SC/APC connectorized
LOCK TYPE	European type cylinder 333 (EN1303) with the possibility of a unified key with a single encryption.







PFS 3



The PFS 3 cabinet allows, on a multi-operator passive network (PON) that supports point-to-point and pointmultipoint technologies, the optical connection of up to 256 HH (secondary network), with the possibility of swapping, between the cables coming from a primary concentration element and the cables directed to the individual HH. It's external case, including door and roof, can be dismounted in case of damage without interrupting the connections inside.



PRODUCT CODE

LNIT-PFS3

TECHNICAL FEATURES	
EXTERNAL DIMENSIONS	110x70x20 cm.
PROTECTION GRADE	IP55 - IK10.
MATERIAL	SUS 304
WEIGHT	40 KG
LOCK TYPE	European type cylinder 333 (EN1303) with the possibility of a unified key with a single encryption.







PFS 4



The PFS 4 cabinet HLGX version allows, on a multi-operator passive network (PON) that supports point-to-point and point-multipoint technologies, the optical connection of up to 256 HH (secondary network), with the possibility of swapping, between the cables coming from a primary concentration element and the cables directed to the individual Real Estate Units.

The cabinet is designed to house up to 24 HGLX 1x16 optical splitters.



PRODUCT CODE

PFS4-PNRR

TECHNICAL FEATURES	
EXTERNAL DIMENSIONS	110x65x20 cm
PROTECTION GRADE	IP55 - IK10.
MATERIAL	Acciaio INOX AISI 304 per l'involucro esterno e per le parti interne.
WEIGHT	RAL 7035
LOCK TYPE	European type cylinder 333 (EN1303) with the possibility of a unified key with a single encryption.








PFS 144



The PFS 144 is a wall/pole mounting cabinet and allows, on a multi-operator passive network (PON) that supports point-to-point and point-multipoint technologies, the optical connection of up to 144 HH (secondary network), with the possibility of swapping, between the cables coming from a primary concentration element and the cables directed to the individual Real Estate Units.

The cabinet is designed to house up to 12 HGLX 1x16 optical splitters.



PRODUCT CODE

OUT-PFS-144FO

TECHNICAL FEATURES	
MATERIAL	SUS 304
EXTERNAL DIMENSIONS	600X600X200 mm (AxLXP)
COLOR	RAL 7035
ADAPTERS QTY	256 SC/APC
SPLICE TRAYS QTY	Splicing/parking area of optical fibers connected to the cabinet, consisting of: -12 PCS GREY (RAL 7035) SC splice trays -6 PCS YELLOW (RAL 1023) SC splice trays -1 PCS RED (RAL 3028) SC splice tray 4 PCS BLUE (RAL 5015) SC splice trays - 2 PCS GREY (RAL 7035) SC splice trays
SPLITTER QTY	Up to 12 pre-installed HLGX type splitters with inputs prepared in the primary network junction area included
LOCK TYPE	European type cylinder 333 (EN1303) with the possibility of a unified key with a single encryption.







F.O. OUTDOOR CABINET

SCP



The New SCP Pole&Street cabinet is designed for distribution and connection of optical fiber. It is intended for outdoor installation on poles or on the ground (as stand-alone).

The cabinet allows, on a multi-operator passive network (PON) that supports point-to-point and multi-point technologies, the optical connection, with the possibility of exchange, between the cables coming from a primary concentration element and the cables directed to the individual customer.





PRODUCT CODE

OUT-SCP-NEW

TECHNICAL FEATURES	
MATERIAL	Alluminun
MATERIAL BOTH POLE FIXING KITS	SUS 304
BASEMENT ACCESSORY	Alluminun
CABLE ENTRY PROTECTION ACCESSORY	Alluminun
COLOR	Light Grey RAL 7035
PROTECTION	IP65 & IK10
MISURE	1200mm (Body) 400mm 300mm (AxLxP)
ADAPTERS QTY	360 SC/APC ports (256 for secondary network, 72 for parking and 24 for primary network)
SPLICE TRAYS QTY	Area di giunzione/parcheggio delle fibre ottiche afferenti all'armadio, costituita da: - Distribution GPON splices: 22 blue trays - Aggregation GPON splices: 4 grey trays - P2P splices: 8 red trays - Parking of unused fibers: 8 yellow trays
SPLITTER QTY	Up to 24 pcs of 1x16 BUTT type optical splitters with pre-connectorized SC/APC input and output
INGRESSI	Top Cable entry Area (which is reversible to have the entrances on the left side or right side): a) 6 round entrances for ADSS cables with diameter up to 16,5 mm b) 1 oval entrances for ADSS cables with diameter up to 16,5 mm Bottom Cable entry Area (which is reversible to have the entrances on the left side or right side): a) 4 round entrances for ADSS cables with diameter up to 16,5 mm b) 2 round entrances for a 24x4/7+1x10/14 mm bundle with diameter up to 45 mm
PROTECTION CLASS	RC2 - IK10 - IP55







NEW SCP - POLE MOUNTING



The New SCP Pole-mounting cabinet is designed for distribution and connection of optical fiber. It is intended for outdoor installation on both concrete and wooden poles. The cabinet allows, on a multi-operator passive network (PON) that supports point-to-point and multi-point technologies, the optical connection of up to 256 HH (secondary network), with the possibility of exchange, between the cables coming from a primary concentration element and the cables directed to the individual customer. The door and the input/output can be changed based on the on-field installation needs. RC2 compliant.





PRODUCT CODE

OUT-SCP-NEW-POLE

110

TECHNICAL FEATURES	
MATERIALE	Esterno: Alluminio Interno: Alluminio
MATERIAL BOTH POLE FIXING KITS	AISI 304 Stainless steel
BASEMENT ACCESSORY	Alluminio
CABLE ENTRY PROTECTION ACCESSORY	Alluminio
COLORE	Light Grey RAL 7035
PROTECTION	IP65 & IK10
MISURE	1200mm (Body) 400mm 300mm (AxLxP)
N° ADATTATORI	360 SC/APC ports (256 for secondary network, 72 for parking and 24 for primary network)
N° SCHEDE DI GIUNZIONE	Area di giunzione/parcheggio delle fibre ottiche afferenti all'armadio, costituita da: - Distribution GPON splices: 22 blue trays - Aggregation GPON splices: 4 grey trays - P2P splices: 8 red trays - Parking of unused fibers: 8 yellow trays
N° SPLITTER	Up to 24 pcs of 1x16 BUTT type optical splitters with pre-connectorized SC/APC input and output
INGRESSI	Top Cable entry Area (which is reversible to have the entrances on the left side or right side): a) 6 round entrances for ADSS cables with diameter up to 16,5 mm b) 1 oval entrances for ADSS cables with diameter up to 16,5 mm Bottom Cable entry Area (which is reversible to have the entrances on the left side or right side): a) 4 round entrances for ADSS cables with diameter up to 16,5 mm b) 2 round entrances for a 24x4/7+1x10/14 mm bundle with diameter up to 45 mm
PROTECTION CLASS	RC2 - IK10 - IP55







E.O. OUTDOOR CABINET

SCP-DG CABINET



The New SCP Pole-mounting cabinet is designed for distribution and connection of optical fiber. It is intended for outdoor installation on both concrete and wooden poles.

The four main areas of the cabinet (cable entry, extra length managing, splicing and splitter) are designed to be completely independent one from the other. To do onfield operations on one of these areas, it is not necessary to operate on the others. Based on our cabinet experience, we designed the cabinet to avoid any movement of the elements inside. The only exception is the splicing panel, that must be open only to open the door, but the cable management is designed to protect all radius of curvatures. Up to 576 splices. RC2 compliant.





PRODUCT CODE

OUT-NEW-SCP-DG

TECHNICAL FEATURES			
MATERIAL - CABINET EXTERNAL	Aluminium		
MATERIAL - CABINET INTERNAL	AISI 430 stainless steel		
BASEMENT ACCESSORY	Aluminium		
HEIGHT	1203mm (Body)		
HEIGHT	2192mm (Total)		
WIDTH	399mm		
DEPTH	299mm		
COLOR	Light Grey RAL 7035		
PROTECTION	IP55 & IK10		







PASSIVE ACCESS NODE (PAN)



The Passive Access Node (PAN) type 2 is a street cabinet designed for distribution and connection of optical fiber. It is intended for outdoor installation on the ground (as stand-alone). It is used for accommodation of the primary network cables and distribution of distributive cables to multi-dwelling or family houses, and it is also used to directly connect users by drop cables suitable for external applications (underground or self-supporting).





PRODUCT CODE

OUT-NEW-SCP

TECHNICAL FEATURES				
MATERIAL	EXTERNAL: SUS 304 INTERNAL: SUS 430			
COLOR	Light Grey RAL 7035			
PROTECTION	IP65 & IK10			
DIMENSIONS	830mm (Body) 400mm 300mm (AxLxP)			







F.O. OUTDOOR CABINET

FWA



L'armadio è un cabinet progettato e realizzato per l'impiego in ambiente esterno e comunque in situazioni non protette da intemperie.

E' utilizzato per alloggiare apparati di telecomunicazione in aree aperte al pubblico o private, lungo le strade e marciapiedi, su terrazzi di edifici o in prossimità dei tralicci.



PRODUCT CODE

OUT-FWA-2023-03

TECHNICAL FEATURES			
MATERIAL	Painted Galvanized Steel		
DIMENSIONI ARMADIO	596x599x1599mm (AxLxP)		
COLOR	RAL 7035		
PROTECTION	IP55/ IK10		
N. OF RACK UNITS	N. 21		
WEIGHT	126 KG (BATTERIES NOT INCLUDED)		







E.O. OUTDOOR CABINET

CABINET IP 65 - 30RU



This is a cabinet specifically designed for use in railways or underground tunnel application, where the temperature range is between 14°C and 20°C, with an heavy presence of dust. The cabinet has a space capacity to house 30 Rack Units and is made up of a single equipment compartment which will contain, in addition to the optical and data transmission equipment, also the electrical panels. It includes a plinth to manage the cable input and output.

This cabinet does not allow air exchange with the outside environment but is equipped with a complex system of heat exchangers that make it able to dissipate the inside thermal power (up to 1.000 W), this solution to prevent dust from entering the cabinet and damaging the equipments inside.



PRODUCT CODE

OUT-ARMADIO TUNNEL GSM-R 29-02-2024

TECHNICAL FEATURES	
DIMENSIONS	750x900x1850 (AxLxP)
DIMENSIONS (HEAT-SINKS INCLUDED)	750x900x1850 (AxLxP)
MATERIAL	Acciaio Zincato verniciato
WEIGHT	220 Kg
COLOR	RAL 7035
THERMAL DATA/OPERATING ENVIRONMENTAL CON-	Potenza dissipabile: W 1200W con CDZ
DITIONS	Temperatura di funzionamento esterna: °C -20 ÷ +45 Altitudine: m l.m. 0 ÷ 800
N. OF RACK UNITS	Totali: NR N. 68
PROTECTION	IP 55 / IK 10







F.O. OUTDOOR CABINET

CABINET IP 55 - 34RU



This is a cabinet designed and built for outdoor usage, it can house 34 RU on the front and 34 RU on the rear, for a total of 68 RU. It has a single equipment compartment which will contain, in addition to the optical and data transmission equipment, also the electrical panels. It includes a 150 mm plinth with a complex system of cable entries meant to guarantee the management and insertion of cables at the base of the cabinet itself.



PRODUCT CODE

-/-

TECHNICAL FEATURES	
DIMENSIONS	750x900x1850 (AxLxP)
DIMENSIONS (HEAT-SINKS INCLUDED)	750x900x1850 (AxLxP)
MATERIAL	Acciaio Zincato verniciato
WEIGHT	220 Kg
COLOR	RAL 7035
THERMAL DATA/OPERATING ENVIRONMENTAL CON-	Potenza dissipabile: W 1200W con CDZ
DITIONS	Temperatura di funzionamento esterna: °C -20 ÷ +45 Altitudine: m l.m. 0 ÷ 800
N. OF RACK UNITS	Totali: NR N. 68
PROTECTION	IP 55 / IK 10







F.O. OUTDOOR CABINET

CABINET IP 55 STANDARD



IP55 freestanding cabinets are designed for industrial applications. Based on the EN60529 standard, they are guaranteed to protect against water and dust with an IP55 rating.

Application areas are semiopen areas such as factories, warehouses, sloping sheds and other conditions where cabinets are not in direct contact with strong weather agents.



PRODUCT CODE

OUT-IP55-FREE STANDING

TECHNICAL FEATURES	
MATERIALE	Metallo zincato e verniciato
DIMENSIONI ESTERNE	600X600xRU mm (LxPxA)
COLORE	RAL 7035 GRIGIO POLVERE
CLASSE DI PROTEZIONE	IP 55 - IK 10
MONTANTI	2 frontali + 2 posteriori
ACCESSORI INCLUSI	Unità di ventilazione pre-installata sotto il tetto.
INGRESSI	n. 2 PG48 (diam. 37-45 mm) + n. 2 PG21 (diam. 13-18 mm) + n. 2 PVC (diam. 7-25 mm)












Data Center and Data Rooms
RACK/ODF
IN-ROW STRUCTURES
CABLE DUCTS
ENERGY MANAGEMENT
FIBER OPTIC MANAGEMENT





Data Center and Data Rooms RACK/ODF

IN-ROW STRUCTURES
CABLE DUCTS
ENERGY MANAGEMENT
FIBER OPTIC MANAGEMENT



NETWORKING RACKS



These cabinets are the result of careful design and a production process carried out using the latest-generation machinery for cutting/bending and welding of sheet metal. Made up of a double welded frame that together with the bottom and the roof form the load-bearing structure of the Rack. Extremely sturdy cabinet, perfect in its geometry, carefully finished, versatile and easy to assemble as well as light in weight. Static load of 800 kg.



- According to the standards: EIA 310-E, IEC 60297, DIN 41494
- Protection degree according to EN60529: IP20
- Elegant design
- Resistant to industrial environments through special phosphate treatments and epoxy powder coating
- Accurate finishes
- Quick and easy assembly
- No special tools are required for assembly
- Robust structure and resistant to a maximum static load of 800 kg.
- Material: cold-rolled steel
- Adjustable cable passage on the lid and bottom
- Interchangeable front/back doors, installable on both the right and left side
- Opening angle of the front door greater than 180°
- Earthing points on the structure and on the doors
- Number of units on the uprights
- Lock with handle
- Round lock for blind door
- Ventilation provided on the lid and bottom
- Glass or perforated doors for high ventilation
- 5mm thick tempered glass
- Side panels removable for easy set-up
- With adjustable feet
- A wide range of accessories available
- Custom models available
- Colours: Black RAL 9004 or Grey RAL 7035
- Delivered in reduced packaging or assembled RoHS







NETWORKING RACKS







19" uprights numbered and adjustable in depth.



Front and rear doors quick release, reversible right/left and interchangeable front/back.



Particular ribbing of the doors, with high ventilation, which gives strength and a pleasant aesthetic.



Removable side panels with snap.



Roof with predisposition for 2 and 4 fan ventilation system.



19" rack system usable on the 4 sides of the rack starting from the 800x800 size (with appropriate adjustments of the uprights).

TECHNICAL FEATURES			
WIDTH	600 o 800 mm		
DEPTH	600 o 800 mm		
HEIGHT	2650mm		
CAPACITY	800KG		

Configurations not present in the catalogue available upon request







DATA CENTER AND SERVER RACKS



The rack cabinets for server rooms and data centers have been designed to be inserted in contexts that are not strictly professional but also suitable for larger work spaces. While maintaining a decidedly high level of quality and technology related to energy saving, we also wanted to favor the aesthetic and ergonomic aspect of the cabinets that, more and more often, are chosen by small/large companies and professionals in the most varied sectors.






RACK CODES



DIMENSIONS NETWORKING		DC & SERVER				
H mm	W mm	D mm	GREY	BLACK	GREY	BLACK
1200	600	1000	F-24U6010-XXX-OT-NE	F-24U6010-XXX-OT-GR	F-24U6010-XXX-IT-NE	F-24U6010-XXX-IT-GR
1200	800	1000	F-24U8010-XXX-OT-NE	F-24U8010-XXX-OT-GR	F-24U8010-XXX-IT-NE	F-24U8010-XXX-IT-GR
1500	600	1000	F-30U6010-XXX-OT-NE	F-30U6010-XXX-OT-GR	F-30U6010-XXX-IT-NE	F-30U6010-XXX-IT-GR
1500	800	1000	F-30U8010-XXX-OT-NE	F-30U8010-XXX-OT-GR	F-30U8010-XXX-IT-NE	F-30U8010-XXX-IT-GR
1800	600	1000	F-37U6010-XXX-OT-NE	F-37U6010-XXX-OT-GR	F-37U6010-XXX-IT-NE	F-37U6010-XXX-IT-GR
1800	800	1000	F-37U8010-XXX-OT-NE	F-37U8010-XXX-OT-GR	F-37U8010-XXX-IT-NE	F-37U8010-XXX-IT-GR
2000	600	1000	F-42U6010-XXX-OT-NE	F-42U6010-XXX-OT-GR	F-42U6010-XXX-IT-NE	F-42U6010-XXX-IT-GR
2000	800	800	F-42U8080-XXX-OT-NE	F-42U8080-XXX-OT-GR	F-42U8080-XXX-IT-NE	F-42U8080-XXX-IT-GR
2000	800	1000	F-42U8010-XXX-IT-NE	F-42U8010-XXX-OT-GR	F-42U8010-XXX-IT-NE	F-42U8010-XXX-IT-GR
2000	800	1200	F-42U8012-XXX-OT-NE	F-42U8012-XXX-OT-GR	F-42U8012-XXX-IT-NE	F-42U8012-XXX-IT-GR
2200	600	1000	F-46U6010-XXX-OT-NE	F-46U6010-XXX-OT-GR	F-46U6010-XXX-IT-NE	F-46U6010-XXX-IT-GR
2200	600	1200	F-46U6012-XXX-OT-NE	F-46U6012-XXX-OT-GR	F-46U6012-XXX-IT-NE	F-46U6012-XXX-IT-GR
2200	800	1000	F-46U8010-XXX-OT-NE	F-46U8010-XXX-OT-GR	F-46U8010-XXX-IT-NE	F-46U8010-XXX-IT-GR
2200	800	1200	F-46U8012-XXX-OT-NE	F-46U8012-XXX-OT-GR	F-46U8012-XXX-IT-NE	F-46U8012-XXX-IT-GR

CODE GENERATION EXAMPLE

The following example refers to a rack with glass front door and rear blind door, BLACK RAL 9005 color, 600x600x1200 mm dimension.



111	GLASS FRONT DOOR - BLIND REAR DOOR
211	VENTED FRONT DOOR - BLIND REAR DOOR
131	GLASS FRONT DOOR - VENTED REAR DOOR
231	VENTED FRONT DOOR - VENTED REAR DOOR
141	GLASS FRONT DOOR - VENTED REAR DOUBLE DOOR
241	VENTED FRONT DOOR - VENTED REAR DOUBLE DOOR
411	VENTED FRONT DOUBLE DOOR - BLIND REAR DOOR
311	BLIND FRONT DOOR - BLIND REAR DOOR
431	VENTED FRONT DOUBLE DOOR - VENTED REAR DOOR
331	BLIND FRONT DOOR - VENTED REAR DOOR
441	VENTED FRONT DOUBLE DOOR - VENTED DOUBLE REAR DOOR
341	BLIND FRONT DOOR - VENTED DOUBLE REAR DOOR







WMA (WALL MOUNTING ASSEMBLED) RACKS




The WMA (WALL MOUNTING ASSEMBLED) series has been designed with a simple structure but with elegantly finished lines, the racks arrive fully assembled and ready to use. Ideal choice for the safe mounting of Routers, Switches, media converters and other Networking and structured cabling equipment.



Capacity (U)	Dimensions	Code
6	600*450*370	WMA-06U6045-SA-NE
6	600*600*370	WMA-06U6060-SA-NE
9	600*450*500	WMA-09U6045-SA-NE
9	600*600*500	WMA-09U6060-SA-NE
12	600*450*635	WMA-12U6045-SA-NE
12	600*600*635	WMA-12U6060-SA-NE

- High Load Capacity
 Highly reliable structure, maximum load capacity of 90
- Robust Structure
 Fully welded and assembled structure.
- Wide door opening
 The front door allows 180 degree opening.



/N	Name	Quantity	
1	Frame		
2	Horizontal bracket	4	
3	Vertical rail	4	
4	Top cover	1	
5	Bottom panel	1	
6	Front door	1	
7	Rear panel	1	
8	Side panel	Side panel 2	
9	Mounting bracket 1		
10	L-shaped bracket	2	







WMD (WALL MOUNTING DISASSEMBLED) RACKS



The WMA (WALL MOUNTING ASSEMBLED) series has been designed with a simple structure but with elegantly finished lines, the racks arrive fully assembled and ready to use. Ideal choice for the safe mounting of Routers, Switches, media converters and other Networking and structured cabling equipment.



Capacity (U)	Dimensions	Code
6	600*450*370	WMD-06U6045-SA-NE
6	600*600*370	WMD-06U6060-SA-NE
9	600*450*500	WMD-09U6045-SA-NE
9	600*600*500	WMD09U6060-SA-NE
12	600*450*635	WMD-12U6045-SA-NE
12	600*600*635	WMD-12U6060-SA-NE

Space Saving

Disassembled racks occupy 1/3 of the volume of assembled ones.

Load capacity


Structure with maximum load capacity of 40 kg.

Wide door opening

The front door allows a 180 degree opening.

Easy Installation

Extremely easy to assemble, a trained person will take about 5 minutes to assemble the rack



/N	Name	Quantity	
1	Frame	2	
2	Horizontal bracket	4	
3	Vertical rail	4	
4	Top cover	1	
5	Bottom panel	1	
6	Front door	1	
7	Rear panel	1	
8	Side panel	2	
9	Mounting bracket	Mounting bracket 1	
10	L-shaped bracket	2	







DATA ROOMS AND DATA CENTERS

ODF DISTRIBUTION FRAME




ODF frame is a 900x300x2.200 mm rack equipped with 19" 47RU uprights where the distance between the pair of rear uprights and the rear panel is 20mm and the distance between the two pairs of uprights is 220mm.

The uprights have 9.5mm square holes. The frame has an optional double-door with 180° opening, door closure with magnets. Standard color is RAL 7035.

PRODUCT CODE

ODF-900x300x2200











DATA ROOMS AND DATA CENTERS

ODF DISTRIBUTION FRAME



FEATURES:

- Fiber curvature radius protected throughout the frame;
- Complete accessibility thanks to the front doors (optional) that can be opened at 180°:
- N.4 300x150 holes for fiber passage on both side walls,
- closeable with special panels;
- N.8 300x100 holes for fiber passage on the back wall, closeable with special panels;
- N.3 horizontal panels for 3RU fiber dispersion supplied;
- Rear panel completely prepared for accompanying tubes in drawers for each of the 47RU;
- Right side of the frame with ring elements for accompanying fibers;
- standard Ral 7035 color;
- Provision for back to back fixing;
- Provision for wall and floor fixing;
- N.3 left side brackets for mounting up to 12 fiber optical dividers;
- Optional 192 FO optical dividers;
- Optional F.O. protection tube;
- Fiber management rings on right front upright available for all 47RU.


COMPLIANCES & CONFORMITIES

- EN 61587 -1:2012 Mechanical Structures for Electronic Equipment;
- IEC 297-2 Overall cabinet dimensions;
- CE conform to EN 60950-1:2006 Information Technology Equipment Safety Part-1-General Requirement;
- UL listed to: UL 2416, Outline of Investigation for Audio/Video, Information and Communication Technology Equipment Cabinet, Enclosure and Rack Systems;
- UL 60950-1 and CSA C22.2 NO.;
- 60950-1-07, Information Technology Equipment Safety Part 1: General requirements;
- ISO9227-ASTM B117-85 Epoxy Polyester Powder Coated 80-120micron-
- 500+ hours Salt Spray resistance to corrosion Operating Temperature -25 °C -+70 °C;
- based on IEC 60068-2-1 cold test- IEC 60068-2-2 dry heat.
- based on IEC 60068-2-1 cold test- IEC 60068-2-2 dry heat.









Data Center and Data Rooms
RACK/ODF

IN-ROW STRUCTURES

CABLE DUCTS
ENERGY MANAGEMENT
FIBER OPTIC MANAGEMENT



DATA ROOMS AND DATA CENTERS


MODULAR IN-ROW MULTI-LAYER STRUCTURE FOR DATA ROOMS



Modular in-row multi-layer structure is designed for installation inside data rooms and shelters / outdoor POPs. It is composed of a load-bearing base (bridge) and a multi-layer upper channel for cable passage and management. The structure is designed for side-to-side, back-to-back mounting and for fixing to the ground and/ or to the wall.

The entire structure is standardly painted with RAL 7035 powder paint, textured finish, minimum thickness 80µm. Other colors available only upon request.





COMPLETE SINGLE-SIDE CONFIGURATION

The complete single-side configuration, with two complete levels, includes:

- 1. Bridge structures of variable length according to the project needs;
- 2. Copper bar for equipotential connection, with relative fixing brackets and insulators;
- 3. First level with full cable tray, dedicated to the FO cables, with relative lateral protection brackets;
- 4. Second level with full cable tray, dedicated to the FO and data cables, with relative lateral protection brackets;
- 5. Descents for the FO, no. 2 for each cabinet foreseen by the project (the number can be changed on request);
- 6. Turrets and shelves for assembling the upper levels;
- 7. Third level with commercial-type wire walkway for energy cables, with relative assembly clamps.

PRODUCT CODE

CODE BASED ON OPTIONS - ASK US A QUOTATION BASED ON YOUR NEEDS

TECHNICAL FEATURES		
WIDTH	900 mm - 1,5 POS 1200 mm - 2 POS 1500 mm - 2,5 POS 1800 mm - 3 POS 2400 mm - 4 POS	
DEPTH	400mm	
HEIGHT	2650mm	







STRUTTURE E POWER MANAGEMENT


MODULAR IN-ROW MULTI-LAYER STRUCTURE FOR DATA ROOMS



Modular in-row multi-layer structure is designed for installation inside data rooms and shelters / outdoor POPs. It is composed of a load-bearing base (bridge) and a multi-layer upper channel for cable passage and management. The structure is designed for side-to-side, back-to-back mounting and for fixing to the ground and/ or to the wall.

The entire structure is standardly painted with RAL 7035 powder paint, textured finish, minimum thickness 80µm. Other colors available only upon request.





COMPLETE DOUBLE-SIDE CONFIGURATION

The complete single-side configuration, with two complete levels, includes:

- 1. Bridge structures of variable length according to the project needs:
- 2. Copper bar for equipotential connection, with relative fixing brackets and insulators;
- 3. First level with full cable tray, dedicated to the FO cables, with relative lateral protection brackets;
- 4. Second level with full cable tray, dedicated to the FO and data cables, with relative lateral protection brackets;
- 5. Descents for the FO, no. 2 for each cabinet foreseen by the project (the number can be changed on request);
- 6. Turrets and shelves for assembling the upper levels;
- 7. Third level with commercial-type wire walkway for energy cables, with relative assembly clamps.

PRODUCT CODE


CODE BASED ON OPTIONS - ASK US A QUOTATION BASED ON YOUR NEEDS

TECHNICAL FEATURES			
WIDTH	900 mm - 1,5 POS 1200 mm - 2 POS 1500 mm - 2,5 POS 1800 mm - 3 POS 2400 mm - 4 POS		
DEPTH	400mm + 400mm = 800mm		
HEIGHT	2650mm		









Data Center and Data Rooms RACK/ODF

IN-ROW STRUCTURES

CABLE DUCTS

ENERGY MANAGEMENT
FIBER OPTIC MANAGEMENT



FIBER MANAGEMENT

YELLOW FIBER DUCTS



Fiber optic fiber ducts are necessary for housing and transportation of fiber optic cables and patch cords and are complete with all the branches, descents, ascents, supports and exits necessary for their installation. They are mostly used in situations such as data rooms, data centers and shelters.



PRODUCT CODE

PLEASE CHECK THE SPECIFIC CATALOGUE

TECHNICAL FEATURES	
FIBER DUCTS TYPE	2"x2" - 4"x4" - 4"x6" - 4"x12"
ACCESSORIES	Planar curve, end caps, coupler, down curve and up curve, Tee, Cross, exits and support bracket
COLOR	Yellow
MATERIAL STRAIGTH SECTION	PVC
MATERIAL ACCESSORIES	ABS
FIRE RESISTANCE	UL94V0









Data Center and Data Rooms
RACK/ODF
IN-ROW STRUCTURES
CABLE DUCTS

ENERGY MANAGEMENT

FIBER OPTIC MANAGEMENT



8+8 MULTI-USER 48VDC SMART PDU - 3RU



8+8 Multi-user 48Vcc SMART PDU can be installed in rack cabinets with 19" (And 21" uprights with adaptation brackets), suitable for redundant power supply of active devices at 48V in DC, with a system for measuring and controlling the supply voltage and the individual absorbed currents.



PRODUCT CODE

PDU48-8+8-2L100A-01

TECHNICAL FEATURES			
DIMENSIONS	139x181x484 mm (HxPxL)		
IP PROTECTION DEGREE	IP 20		
CURRENT RATING	100A		
POWER SUPPLY	Two separate disconnectable lines		
CASE MATERIAL	Galvanized painted steel		
COLOR	RAL 7035		
OPERATING TEMPERATURE RANGE	0+40 °C		
VOLTAGE RATING	48V in Direct Current		







4+4 MULTI-USER 48VCC SMART PDU - 4RU



4+4 Multi-user 48Vcc SMART PDU can be installed in rack cabinets with 19" (And 21" uprights with adaptation brackets), suitable for redundant power supply of active devices at 48V in DC, with a system for measuring and controlling the supply voltage and the individual absorbed currents.



PRODUCT CODE

PDU48-4+4-2L100A-01 New

TECHNICAL FEATURES		
DIMENSIONS	175X185X435 mm (HxPxL)	
IP PROTECTION DEGREE	IP 20	
CURRENT RATING	100A	
POWER SUPPLY	Two separate disconnectable lines	
CASE MATERIAL	Galvanized painted steel	
COLOR	RAL 7035	
OPERATING TEMPERATURE RANGE	0+40 °C	
VOLTAGE RATING	48V in Direct Current	







2+2 MULTI-USER 48VDC PDU - 3RU



2+2 Multi-user 48Vcc PDU can be installed in rack cabinets with 19" (And 21" uprights with adaptation brackets), suitable for redundant power supply of active devices at 48V in DC.



PRODUCT CODE

PDU48-2+2-4RU-200A-NM

TECHNICAL FEATURES		
DIMENSIONS	180x181x484 mm (HxPxL)	
IP PROTECTION DEGREE	IP 20	
CURRENT RATING	100A +100A	
POWER SUPPLY	Two separate disconnectable lines	
CASE MATERIAL	Galvanized painted steel	
COLOR	RAL 7035	
OPERATING TEMPERATURE RANGE	0+40 °C	
VOLTAGE RATING	48V in Direct Current	








5+5 MULTI-USER 48VDC PDU - 3RU



Multi-user PDU that can be installed in rack cabinets with 19" (and 21" uprights with an optional adaptation bracket), it is suitable for redundant power supply of active devices at 48V DC. The multi-user PDU has 2 lines with In=63A, 5+5 fuse holder bases with IN=32A with optical signaling of blown fuse, for power supply and protection of the devices.



PRODUCT CODE

PDU48-5+5-2L-63A

TECHNICAL FEATURES	
DIMENSIONS	175X185X435 mm (HxPxL)
IP PROTECTION DEGREE	IP 20
CURRENT RATING	63A
POWER SUPPLY	Two separate disconnectable lines
CASE MATERIAL	Galvanized painted steel
COLOR	RAL 7035
OPERATING TEMPERATURE RANGE	0+40 °C
VOLTAGE RATING	48V in Direct Current







PDU 230VAC 10 LINES



This PDU can be installed in rack cabinets with 19" (and 21" uprights with an adapter bracket), it is suitable for being powered by an automatic transfer system (ATS), to section and protect 10 devices from short circuits and overloads.



PRODUCT CODE

QA 230Vca-3RU-32A-10UT-001 (BMS ATS)

TECHNICAL FEATURES		
DIMENSIONS	139x181x484 mm (HxPxL)	
IP PROTECTION DEGREE	IP 40	
CURRENT RATING	32A	
POWER SUPPLY	Two separate disconnectable lines	
CASE MATERIAL	Galvanized painted steel	
COLOR	RAL 7035	
OPERATING TEMPERATURE RANGE	0+40 °C	
VOLTAGE RATING	230V in Alternate Current	







HEAD-ROW ELECTRIC PANEL QCC 630A



The QCC receives continuous power from Energy Station 1 and Energy Station 2 and is functional to power the TLC devices installed in the row structures of OLO room.

It can be installed either at the beginning/end of a modular in-row multi-layer structure or independently.

The QCC is equipped with remote monitoring systems for the state of the fuses and consumption measurements.



PRODUCT CODE

QCC48-20+20-630A

TECHNICAL FEATURES	
DIMENSIONS	600X450X2200 (b x p x h)
COLOR	Light Grey ral 7035
IP PROTECTION DEGREE	IP30
CASE MATERIAL	AISI 304
CURRENT RATING	630A
POWER SUPPLY	n. 2 distribution lines
VOLTAGE RATING	48V DC








AUTOMATIC TRANSFER SWITCH (ATS)



ATS – Automatic Transfer Switch – combines the characteristics of data center power management technology with the development of power distribution technology. It applies the latest hot-swappable technology, integrates network communication, remote control and automatic transfer. The power distribution technology in the specially designed Automatic Transfer Switch can be upgraded from local management to remote management upon request with dedicated accessories.



Basic ATS





PRODUCT CODE

ATS-AR228T0122

TECHNICAL FEATURES	
DIMENSIONS	482.6x220x88.8 mm(LxPxA)
RACK UNITs	U2
MOUNTING	19"
TRANSFER TIME	10 ≤ 16 ms
INPUT	IEC60309 32A PLUG
VOLTAGE RATING	180 ~260VAC 50/60Hz
INPUT CURRENT LOAD	32A
OUTPUT CURRENT LOAD	32A
VOLTAGE RATING	IEC60309 32A







DATA CENTER POWER DISTRIBUTION UNITS





230Vac Power Distribution Units (PDUs) are essential devices for efficient power management within rack cabinets, typically used in data centers, server rooms, and IT environments. Designed to ensure safe and reliable power distribution, PDUs allow centralized and organized supply to servers, switches, network equipment, and other electronic devices installed in the rack.

Available in various configurations (horizontal or vertical, with Schuko, IEC C13/C19 outlets, etc.), they may include advanced features such as remote power consumption monitoring, surge protection, or selective outlet switching.

Built to be robust and dependable, our 230Vac PDUs are engineered for professional environments where power continuity and safety are critical.

PRODUCT CODE

Please refer to the specific catalogue













Data Center and Data Rooms
RACK/ODF
IN-ROW STRUCTURES
CABLE DUCTS
ENERGY MANAGEMENT
FIBER OPTIC MANAGEMENT



FO CABLE MANAGEMENT

U-SHAPE



The U-Shape Fiber Slack Storage Device is the protection for ADSS and standard cables installed on the poles. Its scope is the management and the safe routing of the cables those are coming down/up from the pole reversing and storage the cable slack.

Use tie wraps plastic or metallic on the upper external part to store the cables and internal tie wraps plastic or metallic as fixing points at the central position to fix the passing through cables.



PRODUCT CODE

U-SHAPED AEH

TECHNICAL FEATURES	
MATERIAL GF+PP	GF+PP
HEIGHT (overall)	248mm
WIDTH (overall)	345mm
WIDTH (excluding locking system)	374,5mm
DEPTH (overall)	110mm
DEPTH (excluding locking system)	90mm
COLOR	RAL7035, other available
PROTECTION LEVEL	IK10 +UV







24SC PIVOT SUBRACK



The 24-position Compact Optical Module (or MOC) for simplex adapters is a pivot subrack that can be installed on ETSI N3 or 19-inch uprights. It is necessary for the splicing and termination of fibre optic cables and has been designed and developed on the basis of the TIM technical specification.



PRODUCT CODE

MOC-24-TIM / Compact Optical Module (MOC) termination on ETSI N3 and 19" frames with 24 positions for simplex SC adapters - VS 030-1. NMU 774931

TECHNICAL FEATURES		
MATERIAL	STEEL	
OPENING TYPE	Pivot	
HEIGHT	44 mm	
WIDTH	430 MM	
DEPTH	270 MM	
CABLE ENTRANCES	2	
CAPACITY	24	
SPLICE TRAY	2(24FO)	
SMOUV DIMENSIONS	Standard	
ADAPTER	SC SIMPLEX	
COLOR	Grey RAL 7035	







48SC PIVOT SUBRACK



The 24-position Compact Optical Module (or MOC) for duplex adapters is a pivot subrack that can be installed on ETSI N3 or 19-inch uprights. It is necessary for the splicing and termination of fibre optic cables and has been designed and developed on the basis of the TIM technical specification.



PRODUCT CODE

MOC-48 / Compact Optical Module (MOC) termination on ETSI N3 and 19" frames with 24 positions for duplex SC adapters (48 ports).

TECHNICAL FEATURES		
MATERIAL	STEEL	
OPENING TYPE	Pivot	
HEIGHT	44 MM	
WIDTH	430 MM	
DEPTH	270 MM	
CABLE ENTRANCES	2	
CAPACITY	48	
SPLICE TRAY	2 (24FO)	
SMOUV DIMENSIONS	Standard	
ADAPTER	SC DUPLEX	
COLOR	Grey RAL 7035	







TERMINATION/PATCHING OPEN FIBER



The subrack termination has a 90° pivot opening on three fixing points, 1 19" Rack Unit height, the distance from the fixing of the front uprights to the rear ones is 220mm, it is equipped with 48 pre-installed SC/APC simplex type adapters and the internal space to manage the extra-length of cables that will be terminated inside it. This product has been designed and developed on the basis of the Open Fiber technical specification.



PRODUCT CODE

SUB-48SC-TERM / Temination/patching subrack with 48 adapter SC/APC included - OPEN FIBER

TECHNICAL FEATURES		
MATERIAL	Steel	
OPENING TYPE	Pivot on 3 fixing points	
HEIGHT	44 MM	
WIDTH	430 MM	
DEPTH	260 MM	
CABLE ENTRANCES	2 (24 FO)	
CAPACITY	48	
SPLICE TRAY	Not included	
SMOUV DIMENSIONS	/	
ADAPTER	SC Simplex	
COLOR	Grey RAL 7035	








JUNCTION/TERMINATION OPEN FIBER/INFRANEL



The subrack junction and termination has a 90° pivot opening on three fixing points, 1 19" Rack Unit height, the distance from the fixing of the front uprights to the rear ones is 220mm, it is equipped with 48 SC/APC simplex type adapters, 48 pre-installed coloured half-braces and 4 junction cards with 12 positions each. This product was designed and developed on the basis of the Open Fiber/Infratel technical specification.



PRODUCT CODE

SUB3P-A-48SCA-SX-48PTA1-J-T-CD/ Pivot opening subrack, 3 fixing points, for splice and patch, precabled with 48 adapter and 48 pigtails SC/APC – INFRATEL color code for fibers. **SUB3P-A-48SCA-SX-48PTA1-J-T-AB /** Pivot opening subrack, 3 fixing points, for splice and patch, precabled with 48 adapter and 48 pigtails SC/APC – OPEN FIBER color code for fibers.

TECHNICAL FEATURES		
MATERIAL	Steel	
OPENING TYPE	Pivot on 3 fixing points	
HEIGHT	44 MM	
WIDTH	430 MM	
DEPTH	260 MM	
CABLE ENTRANCES	2 (24 FO)	
CAPACITY	48	
SPLICE TRAY	4 (12 FO)	
SMOUV DIMENSIONS	standard	
ADAPTER	SC Simplex	
COLOR	Grey RAL 7035	







24 ADAPTER SC SIMPLEX



The sliding optical subrack for 24 SC Simplex or 24 LC Duplex adapters allows the operator an orderly management and organization system of the optical patchcords. Flexibility and convenience are the main features of the product.



PRODUCT CODE

SUB-1RU-19"-24/48FO-BK / Subrack black color sliding type up to 24 adapter SC simplex type (24 positions) or LC duplex type (48 positions)

SUB-1RU-19"-24/48FO-GR/ Subrack grey color sliding type up to 24 adapter SC simplex type (24 positions) or LC duplex type (48 positions)

TECHNICAL FEATURES		
MATERIAL	Steel	
OPENING TYPE	Sliding	
HEIGHT	44 MM	
WIDTH	434 MM	
DEPTH	243 MM	
CABLE ENTRANCES	2	
CAPACITY	24/48	
SPLICE TRAY	Not included	
SMOUV DIMENSIONS	-	
ADAPTER	SC Simplex / LC Duplex	
COLOR	BLACK RAL9005	







PIVOT 144 ADAPTERS SC SIMPLEX



The subrack with pivot opening allows the operator to work more comfortably once the tray is open, in fact the subrack can be opened by rotating 90°. It can accommodate up to 144 SC Simplex adapters, allows the splicing and termination of fiber optic cables and was designed and developed based on the Infratel technical specification.



PRODUCT CODE

PIV-144-7035 / Subrack Pivot for splicing and termination up to 144 F.O.

TECHNICAL FEATURES		
MATERIAL	Steel	
OPENING TYPE	Pivot	
HEIGHT	132 MM	
WIDTH	482 MM	
DEPTH	270 MM	
CABLE ENTRANCES	2	
CAPACITY	144	
SPLICE TRAY	6 (24FO)	
SMOUV DIMENSIONS	Standard	
ADAPTER	SC Simplex	
COLOR	Grey RAL 7035	







12SC PIVOT SUBRACK



The 12 FO Compact Optical Module (or MOC) for FWA cabinets is a pivot subrack that can be installed on ETSI N3 or 19-inch uprights, it is necessary for the splicing and termination of fiber optic cables, it is equipped with 12 SC/APC simplex adapters, 1 24-splice tray and 4 pre-installed pigtails. This product was designed and developed on the basis of the Open Fiber technical specification.



PRODUCT CODE

MOC-12-12SCA-4PTSCA / Compact Optical Module (MOC) for termination on ETSI N3 and 19 inch frames for FWA cabinets complete with 12 SC/APC simplex adapters and 4 SC/APC pigtails.

TECHNICAL FEATURES	
MATERIAL	Steel
OPENING TYPE	Pivot
HEIGHT	44 MM
WIDTH	430 MM
DEPTH	270 MM
CABLE ENTRANCES	2
CAPACITY	12
SPLICE TRAY	1
SMOUV DIMENSIONS	Standard
ADAPTER	SC Simplex
COLOR	Grey RAL 7035







12 FO WHITE



These splice trays are positioned inside the optical subracks, they can house up to 12 splices, with standard type splice covers, allowing the correct management of the fiber slack of the fibers. They have the possibility to be installed one above on each other, ensuring the opening of each of them, through the hinges that also hook the cover. The cover is included and the product is supplied in white.





PRODUCT CODE

12-24-SPL-TRAY-16 / Splice tray 12 FO white dimensions: 154,5x100,7x14,9mm

TECHNICAL FEATURES		
HEIGHT	14,9 MM	
WIDTH	154,5 MM	
DEPTH	100,7 MM	
MATERIAL	ABS	
COLOR	White	
WEIGHT	60 GR	
OPERATING TEMPERATURE	-40 /+60 °C	
SPLICES	12	
SMOUV DIMENSIONS	Standard	







24 FO BLACK



These splice trays are positioned inside the optical subracks, they can house up to 24 splices, with standard type splice covers, allowing the correct management of the fiber slack of the fibers. They have the possibility to be installed one above on each other, ensuring the opening of each of them, through the hinges that also hook the cover. The cover is included and the product is supplied in black.





PRODUCT CODE

TRAY-STD-SUB-BK / Splice tray 12 FO white dimensions: 156x108x14,6mm

TECHNICAL FEATURES	
ALTEZZA	14,6 mm
LARGHEZZA	156 mm
PROFONDITÀ	108 mm
MATERIALE	ABS
COLORE	Nera
PESO	60 GR
TEMPERATURA DI ESERCIZIO	-40 ÷+60 °C
QUANTITÀ GIUNTI DISPONIBILI	24
DIMENSIONI GIUNTI	Standard







4 MODULES SUBRACK



The sliding subrack 1 rack unit 19" allows the operator an orderly system of management and organization of the cables that are terminated in the rear part of the MPO/LC modules. It can contain up to a maximum of 4 modules. Flexibility and convenience are the main features of the product.



PRODUCT CODE

CHA-MPO-L18 / Sliding subrack for 4 MPO modules.

TECHNICAL FEATURES		
MATERIAL	Steel	
OPENING TYPE	Sliding	
HEIGHT	44 MM	
WIDTH	430 MM	
DEPTH	296 MM	
CABLE ENTRANCES	2	
CAPACITY	4 MPO modules	
SPLICE TRAY	/	
SMOUV DIMENSIONS	/	
ADAPTER	/	
COLOR	Black RAL 9005	







MPO/LC MODULE



The MPO/LC module can contain from a minimum of 1 fan-out with an MPO connector on side A and 12 LC connectors on side B up to a maximum of 2 MPO/LC fan-outs, the adapters such as the polishing of the connectors can be chosen ad hoc based on the requests, OS2, OM3 or OM4 are available.



PRODUCT CODE

REQUEST DATASHEET FOR CODE COMPOSITION

TECHNICAL FEATURES		
HEIGHT	37 MM	
WIDTH	95 MM	
DEPTH	142 MM	
ADAPTER LC QUAD TYPE	MTP/MPO	
OUTPUTS	24	
INPUTS	2	
MATERIAL	Steel	
COLOR	BLACK RAL 9005	








SUBRACK 144 FO MPO



1U SUBRACK 19" rack mounting for 144 FO, it can contain up to 12 modules of 12 slim MPO/LC optical fibres. Both adapters and connectors type can be chosen upon requests: OS2, OM3 or OM4 are available, flexibility and compactness are the key features of this product.



PRODUCT CODE

SUB-MPO-SPL / 1U SUBRACK complete 12 modules of fan-out MPO-LC of 12 FO each

TECHNICAL FEATURES		
MATERIAL	Stainless Steel	
OPENING TYPE	Con Snap Latch	
HEIGHT	44 MM	
WIDTH	430 MM	
DEPTH	390 MM	
CABLE ENTRANCES	2	
MAXIMUM CAPACITY	12	
SPLICE TRAY	1	
HEAT-SHRINKABLE TYPES	Standard	
ADAPTER TYPE	UPON REQUEST	
COLOR	BLACK RAL 9005	







1U FRONT PANEL FOR 4 MPO/LC MODULES



The 1U MPO 19" front panel for smaller subracks allows the operator to have a tidy system of cable management and organization, which are terminated on the rear of the MPO/LC modules. It can contain up to 4 modules. Flexibility and convenience are the key features of the product.



PRODUCT CODE

CHA-MPO-L18 / 1U frontal panel for MPO/LC 12 FO modules

TECHNICAL FEATURES	
HEIGHT	42 MM
WIDTH	485 MM
DEPTH	15,5 MM
CAPACITY	Up to 4 modules
MATERIAL	Stainless Steel
COLOR	Black RAL 9005







BLANK PANEL FOR MODULES



The MPO module blank panel can be inserted inside the 1U MPO front panel and is fixed to it using two snap latch buttons. It allows the holes that are not currently being used by the operator to be closed.



PRODUCT CODE

PAN-PLAIN / Blank panel for MPO modules

TECHNICAL FEATURES	
HEIGHT	25 MM
WIDTH	107 MM
THICKNESS	1,2 MM
CAPACITY	/
MATERIAL	Stainless Steel
COLOR	Black RAL 9005







PANEL FOR 4 MPO ADAPTER



This small panel for 4 MPO adapter can be inserted inside the 1U frontal panel and is fixed to it using two snap latch buttons. It allows to terminate the MPO trunk cables with other cables which then perform the swaps inside the rack (cabinet).



PRODUCT CODE

PAN-4MPO / Panel for 4 MPO adapter

TECHNICAL FEATURES	
HEIGHT	25 MM
WIDTH	107 MM
SPESSORE	1,2 MM
CAPACITY	4 ADAPTER MPO
MATERIAL	Stainless Steel
COLOR	Black RAL 9005







PATCH PANEL - 24 FTP PORTS



19" patch panel complete with 24 shielded RJ45 Cat. 6 connectors, T568A/B universal wiring, 8 contacts, 110 compatible insulation piercing terminals, supports 22 to 26 AWG Cat. 6 shielded twisted pair (FTP) solid and stranded cable - 1 RU.



PRODUCT CODE

PP-C-24-CAT6-FTP / CAT6 FTP 19" 1U 24 ports panel

TECHNICAL FEATURES	
HEIGHT	44,3 MM
WIDTH	482,6 MM
DEPTH	115,8 MM
INPUT	KEYSTONE JACK RJ45 FTP CAT 6
SLOTS	24 CABLES
N. OF CONNECTIONS	24
MATERIAL	Stainless Steel
COLOR	Black RAL 9005







PATCH PANEL RJ45

PATCH PANEL - 24 UTP PORTS



19" Patch panel complete with 24 RJ45 Cat. 6 or Cat. 5E connectors, unshielded, T568A/B universal wiring, 8 contacts, 110 compatible insulation piercing terminals - 1 RU.



PRODUCT CODE

PP-C-24-CAT-UTP / 24 UTP ports patch panel, 1RU, black color, empty

TECHNICAL FEATURES	
HEIGHT	44 MM
WIDTH	482 MM
DEPTH	78 MM
INPUT	KEYSTONE JACK RJ45 CAT 5E - CAT 6
SLOTS	24 Cables
N. OF CONNECTIONS	24
MATERIAL	Stainless Steel
COLOR	Black RAL 9005







KEYSTONE JACK RJ45 UTP



The keystone jack (module) is a standardized snap-in female connector for mounting a variety of low voltage electrical jacks into a patch panel, the rear has an IDC (toolless) cable connection type for ease of installation.





PRODUCT CODE

RJ45-KJ-CAT6 / RJ45 UTP Cat.6 Keystone Jack RJ45-KJ-CAT5 / RJ45 UTP Cat.5e Keystone Jack

TECHNICAL FEATURES	
HEIGHT	19 MM
WIDTH	19 MM
DEPTH	31 MM
CONTACTS	8 CONTACTS - RJ45
CABLES	AWG 22 - 26
COLOR CODE	T568A T568B SCHEMES
DURABILITY	750 SOCKET INSERTS - 25 TERMINATION CYCLES
ELECTRICAL COMPATIBILITY	250 MHZ
MATERIAL	ABS







RACK ACCESSORIES

CABLE MANAGEMENT PANEL 1U



The 19" cable management panel occupies 1 rack unit and has the function of managing cables for the passage from one patch panel to another, meant for both fibre and copper cables. It is made up of 5 front cable management rings which have a cable management DEPTH of approximately 70mm.



PRODUCT CODE

PAN-PASS-5RING-10 / 19" 1U Cable Management, Metal D-rings Product size: 480*46.5*84mm

TECHNICAL FEATURES	
HEIGHT	46,5 MM
WIDTH	480 MM
DEPTH	84 MM
MATERIAL	Metal
COLOR	Black RAL 9005







FLEXIBLANK - 4U FLEXIBLE BLANK PANEL





PRODUCT CODE

F-PAN-4U / Flexible blank panel in plastic material, 4RU, toolless

TECHNICAL FEATURES	
HEIGHT	17,7mm
WIDTH	48mm
COLOR	BLACK
MATERIAL	FIER-PROOF PLASTIC
MOUNTING	19"
MOUNTINGmode	TOOLLESS











FIBER OPTIC CABLES



SINGLE MICRODUCTS



The Microducts are meant for laying mini-optical fiber cables, are produced by extruding high-density polyethylene (HDPE), and are suitable for laying fibers with "blowing" technique (blowing with compressed air).

The Microducts typically used in telecommunications systems have an internal diameter of 10mm (suitable for laying mini-cables up to 144 or 288 optical fibers) while the thickness is established based on their type of use: 10/12mm microducts (thickness 1mm) to be laid in a pipe and 10/14 mini-tube (thickness 2mm) to be buried directly in a trench underground (Direct-Bury).



PRODUCT CODE

MDUCT-12-10-OF / 12/10 mm transparent with BLUE lines - OPEN FIBER

MDUCT-12-10-TIM / 12/10 mm transparent with RED lines - TIM

MDUCT-12-10-FW / 12/10 mm transparent with GREEN lines -

MDUCT-14-10-OF / 14/10 mm transparent with BLUE lines - OPEN FIBER

TECHNICAL FEATURES	12/10 MM 14/10 MM
EXTERNAL DIAMETER	12 mm 14 mm
INTERNAL DIAMETER	10 mm
THICKNESS	1,00 мм 2,00 мм
MATERIAL	PE-HD
COLOR	Depends on the customer network request
TENSILE LOAD	>20 MPa
PULLING	>500%
SOFTENING TEMPERATURE	>120 °C
DENSITY	940 kg/m3
STANDARD LENGHTS	2000 m 1500 m







FENDER MULTI-DUCTS



The FENDER Multi-duct consists of a PEHD tape on which 5 to 7 microducts are neatly positioned, individually fixed by tight wrapping of external tape. This conformation also allows for correct and orderly planar positioning of the cables.



PRODUCT CODE

FENDER-5X10-14-OF/ Fender 5 x 10/14 mm transparent with BLUE lines - OPEN FIBER **FENDER-7X10-14-OF/** Fender 7 x 10/14 mm transparent with BLUE lines - OPEN FIBER

TECHNICAL FEATURES				
	FENDER Multi-duct 10/12		FENDER Multi-duct 10/14	
	Internal	External	Internal	External
DIAMETER	10 mm	12 mm	10 mm	14 mm
N. OF MICRODUCTS	Min 3	Max 5	Min 3	Max 7
THICKNESS	1,00 mm 2,00 mm		nm	
MATERIAL	PE-HD			
COLOR	Depends on the customer network request			
	Open Fiber, FlashFiber e Infratel			
LINES	H 0,1			
SHEATH THICKNESS	Min 0,4 mm Max 0,6 mm			
STANDARD LENGHT	1500 m			







FENDER MULTI-DUCTS



The Bundle Multi-ducts is meant for laying optical minicables and has a PEAD sheath containing 7 minitubes. The minitubes have a smooth external surface and a grooved internal surface to increase the smoothness of the cables deploying during the blowing phase. The loose sheath allows the movement of the tubes in the bundle to adapt their geometry according to the laying needs.



PRODUCT CODE

BUNDLE-7X10-12-OF/ Bundle 7 x 10/12 mm transparent with BLUE lines, external diam. ø 50mm - OPEN FIBER **BUNDLE-7X10-12-TIM /** Bundle 7 x 10/12 mm transparent with RED lines, external diam. ø 50mm - TIM

TECHNICAL FEATURES	12/10 MM	14/10 MM	
DIAMETER	50 mm	12 mm	
N. OF MICRODUCTS	3,00 mm	1,00 mm	
MATERIAL	PE-HD		
COLOR	External sheath Orange – Internal upon request		
	Open Fiber, FlashFiber e Infratel		
TENSILE LOAD	>20 MPa		
PULLING	>500%		
SOFTENING TEMPERATURE	T>120 °C		
DENSITY	> 940 kg/m3		
STANDARD LENGHTS	500 m		







MICRODUCTS CUTTER



The microducts cutter is a tool for cutting minitubes or tubes for vertical applications at 90° and shortening them precisely and without burrs.



PRODUCT CODE

TG-TUB / Tool for miniducts cutting

TECHNICAL FEATURES	
DUCTS DIAMETER	Up to 14 mm
COLOR	BLACK
MATERIAL	Plastic
BLADE	Stainless Steel - Changable







MICRODUCTS CONNECTORS



Microducts fast connectors are needed to connect microtubes together, they have tensile strength and pressure resistance according to the specification. These characteristics make them perfectly performing when using cable blowing machines.



PRODUCT CODE

STR12/10MM / 12 mm ducts **STR14/10MM /** 14 mm ducts

TECHNICAL FEATURES	
MATERIAL	Policarbonato
BLOCKING SYSTEM	POM, with steel teeth
MATERIAL O-RING	O-RING Nitrile
BLOWING PRESSURE	16 bar @ -20 / +50 °C
BREAKING PRESSURE	> 26 bar
GAS SEAL	Leackage at 16 bar: ~1ml/minute – leackage at 0,7 bar: ~0,1ml/minute
WATER RESISTANCE	I giunti resistono ad una colonna d'acqua di 6 metri
INSERTION FORCE	50 N max (5kg)
TENUTA	125N min microdotti 10mm







MICRODUCTS END CAPS



Quick-release caps are necessary for closing microtubes and have a perfectly watertight seal.



PRODUCT CODE

EST 12MM / 12 mm ducts EST 14MM / 14 mm ducts

TECHNICAL FEATURES	
MATERIAL	Polycarbonate
BLOCKING SYSTEM	POM, with steel teeth
MATERIAL O-RING	O-RING Nitrile
BLOWING PRESSURE	16 bar @ -20 / +50 °C
BREAKING PRESSURE	> 26 bar
GAS SEAL	Leackage at 16 bar: ~1ml/minute – leackage at 0,7 bar: ~0,1ml/ minute
WATER RESISTANCE	Up to 6-meter water column
INSERTION FORCE	50 N max (5kg)
TENUTA	125N min microdotti 10mm
TAPPI DI CHIUSURA	Disponibili nelle versioni con diametro: Ø 12mm e Ø 14mm







MICRODUTS REDUCER



Quick release reducers are needed to connect two microtubes with different external diameters, they have tensile strength and pressure resistance. These characteristics make them perfectly performing during the use of cable blowing machines.



PRODUCT CODE

BRE 14-12/10MM / 12-14 mm Ducts

TECHNICAL FEATURES	
MATERIAL	Polycarbonate
BLOCKING SYSTEM	POM, with steel teeth
MATERIAL O-RING	O-RING Nitrile
BLOWING PRESSURE	16 bar @ -20 / +50 °C
BREAKING PRESSURE	> 26 bar
GAS SEAL	Leackage 16 bar: ~1ml/minute – Leackage a 0,7 bar: ~0,1ml/minute
WATER RESISTANCE	Up to 6-meter water column
INSERTION FORCE	50 N max (5kg)
TENUTA	125N min microdotti 10mm
RIDUTTORI	Diametro Esterno/Diametro Interno: 14/12 - 12/10mm







MICRODUTS SEALING FOR MICROCABLES



The quick-release sealing element has the function of sealing the exit of a mini-cable from its microduct, maintaining the watertight seal of the micro-tube.





PRODUCT CODE

SE 12/10MM / 12 mm duct / minicable **SE 14/10MM /** 14 mm duct / minicable

TECHNICAL FEATURES	
MATERIAL	Glass fibre reinforced plastic
MATERIAL GUARNIZIONE	Silicone
PRESSURE	Up to 0.5 bar
WEIGHT	18 GR
CRUSHING RESISTANCE	≥ 1000N, 10 sec
TENSILE RESISTANCE	≥ 100N
MATERIALE	Fibra di vetro







OUTDOOR APPLICATION



The single-fiber cable is used for laying outside buildings in the section that reaches the end user directly. It is equipped with a special sheath to protect the fiber outside. The CAV-EST-1FO-TIM model is produced with G.657 A2 fiber, and it has a CPR certification Cca, s3, d1, a3.



PRODUCT CODE

CAV-EST-1FO-TIM / N.M.U. 773219

TECHNICAL FEATURES	
FIBER TYPE	ITU-T G.657-A2
MINIMUM BENDING RADIUS	20 x Ø
MAXIMUM LOAD	500 N
CRUSHING	500 N/10 cm
ENERGY IMPACT	12 J: N. OF IMPACTS 3
TEMPERATURE	-25 / +70°C var. att. ≤0,1dB/km @1550nm
PICOBREAKOUT DIAMETER	0,85 ± 0,05 MM
INTERNAL JACKET MINMUM THICKNESS	0,6 mm
MIDDLE JACKET MINMUM THICKNESS	0,7 mm
STRENGHT MEMBER (DTEX)	≥4.500
TOTAL CABLE DIAMETER	4,5 (±0,1)
WEIGHT	20 kg/km







INDOOR APPLICATION



The single-fiber cable is used for laying inside buildings in the section that reaches the end user directly. It carries the fiber from the optical distribution box (ODB) installed inside the building to the user socket in the home. It can also be used for branching to the vertical cable floor.

The CAV-INT-1FO-TIM model is produced with G.657 A2 fiber, and it has a CPR certification Cca, s3, d1, a3.



PRODUCT CODE

CAV-INT-1FO-TIM/ N.M.U. 721143

TECHNICAL FEATURES	
FIBER TYPE	ITU-T G.657-A2
MINIMUM BENDING RADIUS	10 mm
TENSILE STRENGTH	150 N Δ att. ≤0,1dB/km
CRUSHING	100 N Δ att. ≤0,1dB/km
ENERGY IMPACT	1 J N° impatti: 3 Δ att. ≤0,1dB/km
TEMPERATURE	-10°C/+60°C Δ att. ≤0,1dB/km
PICOBREAKOUT DIAMETER	0,875±0,10
INTERNAL JACKET MINMUM THICKNESS	0,5
STRENGHT MEMBER (DTEX)	≥4.500
TOTAL CABLE DIAMETER	2,6±0,1
WEIGHT	10 kg/km
COLOR	RAL 9002









OUTDOOR APPLICATION



The riser cable is used for laying outside buildings in the section preceding the arrival at the user. Each fiber is individually reinforced with Kevlar. It is possible to choose it in two configurations of 12 fibers and 24 fibers of 900um depending on how many real estate units to be served. CPR CLASS Cca, s3, d1, a3.





PRODUCT CODE

CAV-EST-12FO-TIM / Outdoor multifiber cable, dark grey color, TOL12 G.657 A2, ST 922/ST 929 with CPR Euroclass Cca, s3, d1, a3 - MOQ 2.000 meters

CAV-EST-24FO-TIM / Outdoor multifiber cable, dark grey color, TOL24 G.657 A2, ST 922/ST 929 with CPR Euroclass Cca, s3, d1, a3 - MOQ 2.000 meters

TECHNICAL FEATURES	
FIBER TYPE	G.657-A2
MINIMUM BENDING RADIUS	5 x Ø cavo
TENSILE STRENGTH	400 N Δ att. ≤0,1db/km
CRUSHING	500 N Δ att. ≤0,1db/km
ENERGY IMPACT	I1 J N° impatti: 3 Δ att. ≤0,1db/km
TEMPERATURE	- 10 / +60°C Δ att. ≤0,1db/km
N. OF PICOBREAKOUT	12 - 16 - 20 - 24 - 32
PICOBREAKOUT DIAMETER	0,875 ± 0,10 mm
CABLE DIAMETER (± 0,2 mm)	6,0 - 7,0 - 8,0 - 8,5 - 9,5
NOMINAL CABLE WEIGHT / km	40 kg/km - 55 kg/km - 70 kg/km - 75 kg/km - 90 kg/km
COLOR	RAL 9002








INDOOR APPLICATION



The riser cable is used for laying inside buildings in the section preceding the arrival at the user. Each fiber is individually reinforced with Kevlar. It is possible to choose it in two configurations of 12 fibers and 24 fibers of 900um depending on how many real estate units to be served and depending on the possibility of passing through the corrugated pipes existing in the vertical section of the building. CPR CLASS Cca, s3, d1, a3.



PRODUCT CODE

CAV-INT-12FO-TIM / Indoor multifiber cable, light grey color, TOL12 G.657 A2, ST 922/ST 929 with CPR Euroclass Cca, s3, d1, a3 - MOQ 2.000 meters

CAV-INT-24FO-TIM / Indoor multifiber cable, light grey color, TOL24 G.657 A2, ST 922/ST 929 with CPR Euroclass Cca, s3, d1, a3 - MOQ 2.000 meters

TECHNICAL FEATURES	
FIBER TYPE	G.657-A2
MINIMUM BENDING RADIUS	5 x Ø cavo
TENSILE STRENGTH	400 N Δ att. ≤0,1db/km
CRUSHING	500 N Δ att. ≤0,1db/km
ENERGY IMPACT	I1 J N° impatti: 3 Δ att. ≤0,1db/km
TEMPERATURE	- 10 / +60°C Δ att. ≤0,1db/km
N. OF PICOBREAKOUT	12 - 16 - 20 - 24 - 32
PICOBREAKOUT DIAMETER	0,875 ± 0,10 mm
CABLE DIAMETER (± 0,2 mm)	6,0 - 7,0 - 8,0 - 8,5 - 9,5
NOMINAL CABLE WEIGHT / km	40 kg/km - 55 kg/km - 70 kg/km - 75 kg/km - 90 kg/km
COLOR	RAL 9002







ADSS



- Loose tubes with 12 optical fibers, filled with thixotropic compound
- Stranded loose tubes with dummies if necessary
- Central strength member made of FRP with PE coating if necessary
- Cable strand: dry, with water blocking yarns and tape
- Outer sheath: Black HDPE, UV resistant, 2 ripcords under sheath

48..72 fibers



96 fibers



144 fibers



192 fibers



PRODUCT CODE

DS-OUT-CABLES-ADSS / -

TECHNICAL FEAT	TURES					
Number of fibers		48	72	96	144	192
						200μm
Loose tubes x fibers		4x12	6x12	8x12	12x12	16x12
Loose tubes / Dummies		4/2	6/0	8/0	12/0	1: 4/2
						O: 12/0
Loose tube Ø	mm	2.1	2.1	2.1	2.1	2.0
Central Strength Member	mm	2.3	2.3	3.5	6.3(3.5)	2.1
Minimum aramid yarns	dtex	≥20000	≥20000	≥20000	≥25000	≥45000
Outer sheath thickness	mm	1.5 1.6 1.8				
Outer diameter (±0.5)	mm	10.3	10.3	11.3	14.4	15.0
Weight /km (± 15%)	kg	87	87	109	162	164







ADSS DROP CABLE 4-12



- Central loose tube with up to 12optical fibers and jelly inside
- Aramid yarns peripheral strength member with water blocking yarns
- Outer sheath: HDPE, anti-UV, 2 ripcords under the sheath
- 2 parallel FRP rods embedded inside outer sheath
- Colored strips (2, Yellow)

4..12 fibers



PRODUCT CODE

DS-OUT-CABLES-ADSS-DROP-4-12 / -

TECHNICAL FEATUR	ES		
Number of fibers	4	8	12
PBT Tube Ø	2.5mm	2.5mm	2.5mm
Outer sheath thickness	Nom 1.4mm	Nom 1.4mm	Nom 1.4mm
Outer diameter	7.0±0.3mm	7.0±0.3mm	7.0±0.3mm
Weight (±10%)	40kg/km	40kg/km	43kg/km







ADSS DROP CABLE 24-48



Outdoor aerial installation - 75m span length, NESC Medium, 1% installation sag

- Loose tubes with 12 optical fibers, filled with thixotropic compound
- Stranded loose tubes with dummies if necessary
- Central strength member made of FRP with PE coating if necessary
- Cable strand: dry, with water blocking yarns and tape
- Outer sheath: Black HDPE, UV resistant, 2 ripcords under sheath





PRODUCT CODE

DS-OUT-CABLES-ADSS-DROP-24-48 / -

TECHNICAL FEATUR	ES		
Number of fibers	24	36	48
Module Ø	1.35mm		
Outer sheath thickness	Nom 2.0mm (FRP portion)		
Outer diameter	7.7±0.5mm	7.9±0.5mm	8.3±0.5mm
Weight (±10%)	43kg/km	46kg/km	50kg/km











FIBER OPTIC INSTRUMENTS FOR INSTALLERS



CLADDING ALIGNMENT - FTTH



This cladding-aligned fusion splicer is designed to work every day for fiber optic splicing. It is small and easy to carry and very robust even if the splicing is performed in the field.

This splicer is innovative for fiber optic splicing especially in the creation of FTTH networks for its ease of handling, reliability and the low investment.



ACCESSORY

SHOULDER STRAP FOR SPLICER MACHINESPLICER MACHINE



HOL-CON-SUM

HOL-CON-FUJ

PRODUCT CODE

FS-EA-SPL-MK2 / FTTH Splicer machine FS-EA-SPL-SC / Shoulder strap HOL-CON-SUM / Sumitomo SOC holder HOL-CON-FUJ / Fujlkura SOC holder

TECHNICAL FEATURES	
SPLICING METHOD	V-GROVE (CLADDING)
FIBER TYPE	SMF, MMF 50/125 μm fiber, 250 μm primary jacket and 900 μm secondary jacket
ACCESSORIES INCLUDED	Fiber holders 2 types (250µm and 900µm loose type), stripper, cutter
SPLICING SET UPS	2 presets: SMF & MMF
TYPICAL LOSS	0.03dB SMF, 0.01dB MMF
TYPICAL SPLICING TIME	7s + 50s (splicing time + shrinking time in the stove)
SLEEVES DIMENSIONS	Max 64mm, 2-5mm diameter supported by the stove
INTERFACE	USB, mini usb
INTERNAL MEMORY	1MB, External SD-Card
MONITOR	Color LCD, 2.8", 320×240 pixels
	Camera 140x
OPERATING TEMPERATURES	0-40°C, max 95% RH
WEIGHT	800g
DIMENSIONS	230x98x53mm







SPLICING MACHINES

CORE ALIGNMENT - FTTH



This latest-generation fusion splicer, with six-axis positioning, allows fusion on the fiber core in 7 seconds. Lightweight and compact in size, the splicer offers great resistance to shocks and dust. It can splice any type of fiber with very low attenuation thanks to its high level of precision. This type of splicer allows you to operate effectively in work environments such as construction sites and road manholes.



PRODUCT CODE

FOSM-740 / Core alignment splicer machine

TECHNICAL FEATURES	
SPLICING METHOD	PAS Technology (core alignment)
FIBER TYPE	SSMF, MMF 50/125 μm fiber, 250 μm primary jacket and 900 μm secondary jacket
ACCESSORIES INCLUDED	stripper, cutter, charger, carrying bag
SPLICING SET UPS	2 presets: SMF & MMF
TYPICAL LOSS	0.02dB SMF, 0.01dB MMF, E 0.05dB DS/NZDS/G.655/G.657
TYPICAL SPLICING TIME	7s + 30s (splicing time + shrinking time in the stove)
SLEEVES DIMENSIONS	Max 64mm length, 2-5mm diameter supported by the stove
INTERFACE	USB, mini usb
INTERNAL MEMORY	10.000 splices
MONITOR	4.3" color TFT
	Camera 140x
OPERATING TEMPERATURES	-18°C / + 50°C
WEIGHT	2000g (battery included)
DIMENSIONS	122x122x130mm







FIBER CLEAVER FOR FMC



The fiber optic cleaver is an high-precision tool that allows cutting the optical fiber at adjustable distances depending on the splicer used, it also allows the replacement of the holder with the one supplied with the mechanical connectors.



PRODUCT CODE

TGL-10

TECHNICAL FEATURES	
HEIGHT	60 mm
WIDTH	56 mm
DEPTH	62 mm
WEIGHT	180 gr
COMPATILE FIBER/CABLES	250μm fibre, 900μm fibre, pigtails, drop cables
COMPATILE FIBER DIAMETER	125 μm
CUT LENGHT RANGE	5 ÷ 20
CUT ANGLE GUARANTEED	Max 0.5







FIELD OPTICAL SOURCE



An optical source is an instrument that emits light through a diode or LED at a predetermined wavelength with maximum stability over time in order to measure the optical power and the relative attenuation through an optical power meter or power meter positioned at the other end of the network.

The measuring instrument is able to operate in 4 different wavelengths and can be used in applications with single-mode and multi-mode optical fiber.



PRODUCT CODE

OPT-POW-MET-01 / Highly stable field light source supporting two wavelengths @1310nm and @1550nm

TECHNICAL FEATURES	
WAVELENGHT	1310/1550 nm
SOURCE / DETECTOR	FP-LD
POWER	> -5 dBm @ 1310/1550nm frequency modulation
	CW / 270Hz,1KHz,2KHz
OPTICAL INTERFACE	FC/PC standard - SC/PC optional
OPERATING TEMPERATURE RANGE	-10 ÷ +60 °C
STOCKING TEMPERATURE RANGE	-25 ÷ +70 °C
AUTOMATIC SHUT-OFF TIME	10 min
BATTERYTIME	60h
DIMENSIONS	155x 76 x 38 mm
POWER SUPPLY	Alkaline batteries (3 AA 1.5V)
WEIGHT (G)	300







FIELD POWER METER



An optical power meter or power meter is an instrument used to measure the power in an optical signal. The calibrated sensor inside it consists mainly of a photodiode selected for the appropriate wavelength range and power levels. On the display, the measured optical power and set wavelength are shown.



PRODUCT CODE

OPT-LIGH-SOU-01

TECHNICAL FEATURES	
WAVELENGHT	850÷1650 nm (850/980/1310/1490/1550/1625)
	Risoluzione 0.01 dBm
SOURCE / DETECTOR	InGaAs
POWER	-70 ÷ +10 dBm
OPTICAL INTERFACE	FC/SC
OPERATING TEMPERATURE RANGE	-10 ÷ +60 °C
STOCKING TEMPERATURE RANGE	-25 ÷ +70 °C
AUTOMATIC SHUT-OFF TIME	10 min
BATTERY TIME	200h
DIMENSIONS	155X 76 X 38 MM
POWER SUPPLY	Alkaline batteries (3 AA 1.5V)
WEIGHT (G)	300







INSTRUMENTS

VISUAL FAULT LOCATOR



The visual or laser fault locator is a tool used to locate fiber faults or stresses due to breaks or unauthorized bending radii.



PRODUCT CODE

VIS-FAULT-LOC-03

TECHNICAL FEATURES	
COMPATIBLE CONNECTORS	Con ferula ø 1,25mm - Con ferula ø 2,5mm
WAVELENGHT	650 ±20 nm
OUTPUT POWER	> 1mW
DISTANCE COVERED	5 - 7 Km
MODULATION	Fissa o pulsata
STOCKING TEMPERATURES	-20 / +70 °C - <90% Rh
OPERATING TEMPERATURES	-10 / +60 °C - <90% rh
POWER SUPPLY	n.2 batterie AA
WEIGHT	(GR) 125







FTTX INSTRUMENS






















ISTRUMENTS AND TOOLS

FTTX INSTRUMENS

























Phone +39 0690405273

info@outline.company - www.outline.company

Via degli Olmetti, 39D - 00060 Formello (RM)