

OPTICAL CLOSURE

SPLICES / 3+1 INPUT



The compact 48-junction, with 3 round inlet and 1 oval inlet, optical closure is a passive and watertight F.O. box, which guarantees a high degree of IP protection and therefore impermeability to external agents such as water, dust, humidity and extreme temperatures. It guarantee a resistance capacity range from -40° to 70°. Supplied with splice trays, heat-shrink kits for cable entry and a pole or wall anchoring kit, it is mainly used in hostile environments, ensuring the management and operability of the fiber in safety.



PRODUCT CODE

Q-CL-03 / OPTICAL CLOSURE up to 48 splices with 3 circular input and 1 oval input

TECHNICAL FEATURES

OVAL INPUTS	1
ROUND INPUTS	3
OVERALL DIAMETER (INCLUDING CLAMP)	188
OVERALL HEIGHT (INCLUDING BASE)	300
OVAL INPUT DIAMETER FOR HEAT-SHRINKABLE APPLICATION	20
ROUND INPUT DIAMETER FOR HEAT-SHRINKABLE APPLICATION	16
SPLICE TRAYS	4
MAX SPLICE CAPACITY FOR EACH TRAY	12 F.O.
MAX SPLICING CAPACITY	up to 48 F.O

