



CODE: KIT CONN-SOC-SCA



PRODUCT DATA

FIBER TYPE	850 ~ 950 μm
INSERTION LOSS	(@1310-1550 NM) \leq 0.25 dB
RETURN LOSS	(@1310-1550 NM) \geq 60 dB
INSTALLATION TIME	\leq 4 min.
FERRULE	Pre-polished SC/APC
COUPLING SYSTEM	Splicing

PRODUCT DESCRIPTION

OUT LINE Splice-On connector (SOC) can be mounted directly on the field, using a fusion splice machine such as Fujikura, Sumitomo and Inno brands. A pre-lapped ferrule is supplied from the factory with all the accessories to complete a connector by installing it on a 900 μm cable, the kit also includes the support to hold the ferrule on the splicer (holder).

The installation time is very fast, less than 4 minutes.

DETAILS:

- Can be installed on \varnothing 0,9mm FO cables
- Compatible with SM fibers G. 652 D, G. 657 A1 and G. 657 A2
- Installation time: less than 4 minutes
- Average insertion loss \leq 0.15 dB
- Average return loss \geq 60 dB
- Pulling stress resistance up to \varnothing 0,9mm \geq 5N
- Operating temperatures between +70°C/-25°C
- KIT content:

100pcs SC/APC Splice-on connectors
10pz holders

REFERENCE REGULATIONS:

- ST 986 FIBERCOP

