



PRODUCT CODE

PC-1-SCA-LCA-SM-B3-09-N-TR-1000 / Patchcord SC/APC-LC/APC simplex 0,9mm diameter G657B3 fiber 10-meters length color transparent in a transparent reel

PC-1-SCA-LCA-SM-B3-09-N-TR-2000 / Patchcord SC/APC-LC/APC simplex 0,9mm diameter G657B3 fiber 20-meters length color transparent in a transparent reel

PC-1-SCA-LCA-SM-B3-09-N-TR-3000 / Patchcord SC/APC-LC/APC simplex 0,9mm diameter G657B3 fiber 30-meters length color transparent in a transparent reel

PC-1-SCA-LCA-SM-B3-09-N-TR-4000 / Patchcord SC/APC-LC/APC simplex 0,9mm diameter G657B3 fiber 40-meters length color transparent in a transparent reel

CODE: PC-1-SCA-LCA-SM-B3-09-N-TR-5000 / Patchcord SC/APC-LC/APC simplex 0,9mm diameter G657B3 fiber 50-meters length color transparent in a transparent reel

PARAMETRS	UNIT	SPECIFICATIONS
FIBER		SM G.657 B3
LENGHT	m	Different lenghts described below
COATING DIAMETER	µm	900
COATING COLOR		Transparent
IL @ 1550nm	dB	< 0,3
IL @ 1310 nm	dB	< 0,3
ORL APC @ 1310 AND 1550nm	dB	>60
BENDING RADIUS	mm	$5 \leq R \leq 12$
FIBER HEIGHT	nm	$100 \leq H \leq +100$
APEX OFFSET	mm	$0 \div 50$
ANGLE (APC)	deg	$7.75 \div 8.25$
MAX ROUGHNESS	µm	0,05
MISALIGNMENT KEY ERROR	deg	$0.5 \leq K \leq 0.5$
OPERATING TEMPERATURE		-40~+60 °C
OPERATING HUMIDITY		5~95%RH
STORAGE TEMPERATURE		-40~+85 °C
STORAGE HUMIDITY		5~95%RH
PLUG TYPE		SIDE A: SC/APC; SIDE B: LC/APC